



V-ZUG Australia Pty. Ltd
2/796 High Street East Kew Vic 3102, VICTORIA/Australia
Phone +61 (03) 9832 7500
service.au@vzug.com, www.vzug.com

Brochure CombiCookTop V4000 I804



Selected product

- Article no.: 3109600002
- EAN code: 7630029457573
- Type: CCT4T-31096
- Product category: Hob
- OptiGlass
- Standard width: 80 cm
- Front design: BlackDesign
- Frame: DualDesign



Details CombiCookTop V4000 I804

Compliant to regulation

- (EU) Nr. 66/2014
- GB 21456-2008: No

Design

- Type: CCT4T-31096
- Product category: Hob
- OptiGlass
- Standard width: 80 cm
- Front design: BlackDesign
- Frame: DualDesign

Dimensions

- Cut-out height: 8.5 mm
- Cut-out radius: 5 mm
- Appliance height: 206 mm
- Appliance width: 761 mm
- Appliance depth: 501 mm
- Appliance corner radius: 2 mm
- Support size width: 750 mm
- Max. support size width: 750 mm
- Support size depth: 490 mm
- Max. support size depth: 490 mm
- Installation height when flush-fitted: 206 mm
- Installation height when surface-mounted: 202 mm
- Cut-out width when flush-mounted: 767 mm
- Cut-out width when surface-mounted: 750 mm
- Max. cut-out width when surface-mounted: 750 mm
- Cut-out depth when flush-mounted: 507 mm
- Cut-out depth when surface-mounted: 490 mm
- Max. cut-out depth when surface-mounted: 490 mm
- Empty weight: 19.82 kg
- Cooking zone 1 position: left
- Cooking zone 1 dimensions: 22.0 x 37.0 cm
- Cooking zone 2 dimensions: 22.0 x 37.0 cm

Display and operation

- Display: Graphic touch display
- Controls: Single slider
- Slider control
- Operating time
- Number of languages in display: 12
- Languages in display: DE, FR, IT, RM, EN, ES, NL, RU, UA, ZH, HE, TR
- Button sound (on/off)

Energy

- Output - standby off: 0.29 W
- Consumption when off: 0 W
- Energy efficiency class: A
- Annual energy consumption: 34.1 kWh
- Fluid dynamic efficiency: 31.7
- Fluid dynamic efficiency rating: A
- Cooking zone 1 max. power: 3700 W
- Cooking zone 2 max. power: 3500 W
- Type of connection (1): 220-240 V~
- Frequency (1): 50 Hz
- Connected loads (1): 7.4 kW
- Fuse protection (1): 32 A
- Plug type: Cable
- Cooking zone 1 energy consumption: 658440 J/kg
- Cooking zone 2 energy consumption: 662400 J/kg



Hob features

- Dishwasher-safe metal grease filter cartridge
- metal grease filter cartridge
- Induction coil type: ZoneFlex
- OptiGlass
- Hob category: Induction with integrated range hood
- Operating time with shut-down function
- Residual heat indicator
- Timer
- Restore function
- Cooking zones: 4
- Power levels: 9 + i
- EcoStandby
- Heating technology: Induction cooking zones

Range hood features

- Power levels: 9 + i
- EcoStandby

Functions

- Defrosting
- Warming function
- Automatic pan detection
- Automatic bridging function
- OptiLink
- Heating function
- MemoryFunction
- Extracted air
- Recirculation air
- Powerplus
- CookingControl
- Safety package
- Pause button
- Automatic warm-up function
- Cleaning lock
- Melt function
- Simmer function
- Childproof lock

Additional data

- Collection tray with liquid absorption capacity: 0.35 l
- Metal grease filter cartridge, liquid absorption capacity: 0.175 l
- Total liquid absorption: 0.525 l
- Grease absorption capacity rating: B
- Extracted air output, intensive setting: 595.6 m³/h
- Extracted air output, max. setting: 520.9 m³/h
- Extracted air output, min. setting: 130.8 m³/h
- Recirculation air output, intensive setting: 551.6 m³/h
- Recirculation air output, max. setting: 454.8 m³/h
- Recirculation air output, min. setting: 82.4 m³/h
- Extracted air noise output, intensive setting: 70 dB(A)
- Extracted air noise level, max. setting: 67 dB(A)
- Extracted air noise output, min. setting: 34 dB(A)
- Recirculation air noise output, intensive setting: 66 dB(A)
- Schalleistung Umluft max. Stufe: 61 dB(A)
- Recirculation air noise output, min. setting: 32 dB(A)
- Feature level: 4

Service and interfaces

- Warranty: 2 + 8 years