



Color Variants

BOP251111
Full glass door in Gaggenau Metallic
Width 60 cm
BOP251101
Full glass door in Gaggenau Anthracite
Width 60 cm
BOP251131
Full glass door in Gaggenau Silver
Width 60 cm

Included accessories

1 x enamel baking tray. suit. pyrolitic clean.
1 x glass pan.
1 x grill shelf.
1 x pluggable meat probe.

Optional accessories

BA016105
Pull-out system
BA026115
Baking tray, enamelled
BA036105
Wire rack, chromium-plated
BA046115
Glass tray
BA056115
Heating element for baking stone and Gastronorm roaster.
BA226105
Grill tray, enamelled
BS020002
Pizza paddle, set of 2.
GN340230
Gastronorm roaster in cast aluminium.

Product Variants

BOP250111
Oven 200 series
Full glass door in Gaggenau Metallic
Width 60 cm
Right-hinged

BOP251111
Oven 200 series
Full glass door in Gaggenau Metallic
Width 60 cm
Left-hinged

Flush installation
Pyrolytic system
13 heating methods, with core temperature probe and baking stone function
TFT touch display
Panel-free appliance with surface control module
Electronic temperature control from 30 °C to 300 °C
Net volume 76 litres

Heating methods

Hot air.
Eco hot air.
Top + bottom heat.
Top heat.
Bottom heat.
Hot air + bottom heat.
Full surface grill + circulated air.
Full surface grill.
Compact grill.
Baking stone function.
Roaster function.
Dough proofing.
Defrosting.

Handling

Rotary knob and TFT touch display operation.
Clear text display.
Option to save individual recipes (incl. core temperature probe).
Information key with use indicators.
Side-opening door opens up to 110° angle.

Features

Core temperature probe with automatic shut-off.
Baking stone socket.
Actual temperature display.
Rapid heating.
Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer.
60 W halogen light on the top.
Enamelled side shelf supports with 4 tray levels, pyrolysis-safe.

Safety

Thermally insulated door with quintuple glazing.
Child lock.
Safety shut-off.
Cooled housing with temperature protection.

Cleaning

Pyrolytic system.
Gaggenau enamel.
Heated catalyser to clean the oven air.

Planning notes

Door hinge not reversible.
The door panel surface of the appliance extends 21 mm from the furniture cavity.
The outer edge of the door handle extends 72 mm from the furniture cavity.
Necessary lateral gap between appliance door and furniture panel of min. 5 mm.
Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance.
When planning a corner solution, pay attention to the 110° door opening angle.

Characteristics
Color / Material Front
Stainless steel
Built-in / Free-standing
Built-in
Integrated Cleaning system
Pyrolytic
Required niche size for installation (HxWxD)
590-590 x 560-560 x 550
Dimensions of the product (mm)
595 x 590 x 547
Dimensions of the packed product (HxWxD) (mm)
780 x 760 x 680
Control Panel Material
without panel
Door Material
Glass
Net weight (kg)
55.0
Usable volume of cavity (l)
76
Cooking method
Baking stone function, Bottom heat, Conventional heat, Defrost, Dough proving setting, Full width grill, Half width grill, Hot Air, Hot air and 1/1 bottom heating, Hot Air-Eco, Hot air grilling, Roaster function, Top heat
First cavity material
Enamelled
Temperature control
electronic
Number of interior lights
1
Approval certificates
Australia Standards, CE, Eurasian, G- Mark, Ukraine, VDE
Length electrical supply cord (cm)
Interior Lights - cavity 1
1
Pull-out system
Accessory
Clock function
Alarm, Off, On, timer
Included accessories cavity 1
1 x enamel baking tray,suit. pyrolitic clean, 1 x glass pan, 1 x grill shelf, 1 x pluggable meat probe
Bake Element Wattages cavity 1 (W)
Broil Element Wattages cavity 1 (W)
3000
Convection Element Wattages cavity 1 (W)
2100
Microwave wattage cavity 1 (W)
Drawer wattage (W)
Consumption and connection features
Energy efficiency class - NEW (2010/30/EC)
A
Energy consumption per cycle conventional - NEW (2010/30/EC)
1.25
Energy consumption gas oven per cycle conventional - NEW (2010/30/EC)
Energy consumption per cycle forced air convection - NEW (2010/30/EC)
0.92
Energy consumption gas oven per cycle forced air convection - NEW (2010/30/ EC)
Energy efficiency index (2010/30/EC)
105.7
Electrical connection rating (W)
3700
Current (A)
16
Voltage (V)
220-240
Frequency (Hz)
50
Plug type
fixed connection, no plug
Universal Product Code
825225914792
Color / Material Front
Stainless steel
Alternative colors available
BOP251101, BOP251131

For installation underneath cooktops:
Distance between the underside of the
cooktop and the top edge of the oven
cavity: min. 15 mm. The planning notes
for the cooktops (particularly regarding
ventilation, gas/electric connection)
must be taken into account.
To achieve the 550 mm installation
depth, the connection cable needs to
follow the slanted edge on the corner
of the housing.
The mains socket needs to be planned
outside of the built-in niche.

Connection

Energy efficiency class A at a range of
energy efficiency classes from A+++ to
D.
Total connected load 3.7 kW.
Plan a connection cable.

