

	<div> <div>AC200160</div> <div>Canopy extractor 200 series</div> <div>Stainless steel and glass</div> <div>Width 52 cm</div> <div>Air extraction / Air recirculation</div> </div>		<div> <div>Characteristics</div> <div>Product name/family</div> <div>Color chimney</div> <div>Typology</div> <div>Traditional</div> <div>Approval certificates</div> <div>CE, Eurasian, G-Mark, Ukraine</div> <div>Length electrical supply cord (cm)</div> <div>100</div> <div>Required niche size for installation (HxWxD)</div> <div>418mm x 496mm x 264mm</div> <div>Height of the chimney (mm)</div> <div>Height of product, without chimney (mm)</div> <div>Minimum distance above an electric hob</div> <div>500</div> <div>Minimum distance above a gas hob</div> <div>650</div> <div>Net weight (kg)</div> <div>10.0</div> <div>Type of control</div> <div>Electronic</div> <div>Number of speed settings</div> <div>Maximum output air extraction (m3/h)</div> <div>550</div> <div>Boost position output recirculating (m3/h)</div> <div>690</div> <div>Maximum output recirculating air (m3/h)</div> <div>550</div> <div>Boost position air extraction (m³/h)</div> <div>720</div> <div>Number of lights</div> <div>2</div> <div>Noise level (dB)</div> <div>67</div> <div>Diameter of air outlet (mm)</div> <div>120 / 150</div> <div>Grease filter material</div> <div>Washable aluminium</div> <div>EAN code</div> <div>4242006257460</div> </div>	<div> <div>Total connected load 272 W.</div> <div>Connecting cable 1.0 m with plug.</div> </div>
	<div> <div>Can be integrated invisibly in upper cabinet</div> <div>Energy-saving, low-noise fan</div> <div>Rim extraction with flat and easy-to-clean glass cover</div> <div>Dimmable, neutral white LED light for ideal illumination of the whole cooktop</div> <div>Air extraction or air recirculation system</div> </div>			
<div> <div>Color Variants</div> <div>AC200160</div> <div>Stainless steel and glass</div> <div>Width 52 cm</div> </div>	<div> <div>Output</div> <div>Performance and noise level, output level 3/Intensive:</div> <div>Air output according to EN 61591.</div> <div>Sound power level according to EN 60704-3.</div> <div>Sound pressure level according to EN 60704-2-13.</div> <div>Odour reduction for air recirculation in accordance with EN 61591.</div> <div>Air extraction:</div> <div>550 / 720 m³/h.</div> <div>67 / 72 dB (A) re 1 pW.</div> <div>53 / 58 dB (A) re 20 µPa.</div> <div>Air recirculation:</div> <div>550 / 690 m³/h.</div> <div>72 / 77 dB (A) re 1 pW.</div> <div>58 / 63 dB (A) re 20 µPa.</div> <div>Odour reduction air recirculation 92 %.</div> </div>			
<div> <div>Optional accessories</div> <div>AA200510</div> <div>Remote control for canopy extractor AC200</div> <div>AA210110</div> <div>1 activated charcoal filter with high efficient odour reduction due to increased surface. For air recirculation module AA 211 812.</div> <div>AA211812</div> <div>Patented air recirculation module including 1 activated charcoal filter with high efficient odour reduction due to increased surface</div> </div>	<div> <div>Features</div> <div>3 electronically controlled power levels and 1 intensive mode.</div> <div>Remote control is available as a special accessory.</div> <div>Interval ventilation, 6 min.</div> <div>Run-on function, 6 min.</div> <div>Grease filter saturation indicator.</div> <div>Metal grease filter, dishwasher-safe.</div> <div>Glas filter cover.</div> <div>Neutral white LED light (4000 K), dimmable.</div> <div>Lamp output 2 x 1 W.</div> <div>Illuminance 244 lx.</div> <div>Fan technology with highly efficient, brushless DC motor (BLDC).</div> </div>			
	<div> <div>Consumption data</div> <div>Energy consumption 47.2 kwh/year.</div> <div>Sound level min. 44 dB / max. 67 dB normal mode.</div> </div>			
	<div> <div>Planning notes</div> <div>Patented air recirculation module with activated charcoal filter can be installed in the upper cabinet. The activated carbon filter can be changed from the front by simply pulling out the filter drawer.</div> <div>The door of the upper cabinet must be fully open in order to change the activated charcoal filter.</div> <div>Can be integrated invisibly in upper cabinet.</div> <div>Vario cooktops with intensive production of vapours like VR/VP/VF should be placed in the middle beneath the hood (in this case air recirculation is not recommended).</div> <div>Clearance above gas appliances min. 65 cm (more than total load gas 12 kW min. 70 cm).</div> <div>Clearance above electric appliances min. 50 cm.</div> <div>When installing a ventilation hood with air extraction mode and a chimney-vented fireplace, the power supply line of the ventilation appliance needs a suitable safety switch.</div> </div>			
	<div> <div>Connection</div> </div>			

AC200160

Canopy extractor 200 series

Stainless steel and glass

Width 52 cm

Air extraction / Air recirculation

2018-05-21

Page 2

