

W4104C.W.AU

General description

Product group: Washing Machine Installation type: Freestanding Capacity: 10 kg Spin speed: 1400 rpm 21 programs Available colour: White

Programs, options and modes

Mix/synthetics Wool/hand wash Dark wash Bedding Time program Auto

Quick Heavy Rinse Spin

Easy care Drum cleaning Jeans Shirts

Hygiene

Quick Pro Anti-allergy program cotton Anti-allergy program synthetic Steam refresh

Additional options

Spin speed: Adjustable spin speed Super rinse function Super wash High water level Prewash Anticrease system

Run modes
Normal mode, Green mode, Allergy mode, Speed mode, Intensive mode

Construction & Performance
Quattro™ Construction – vibration-free spinning
Door sealing: Steel seal - hygienic door sealing Long lasting stainless steel drum Cast iron Active Drum technology

Heater capacity (W): 2000 W
Precise temperature control (max deviation: +/- 1 °C) Water level sensor

Drum volume: 80 I Drum volume: 2,8 cu ft Durable brushless moto

Use & Flexibility

Easy close door Slide-in storage for liquid detergent wall Temperature range (°C): Cold -90c Door diameter: 31 cm Door opening angle: 110 °

Interaction & Contro

Up to 24 hours Remaining time indicator Display type: LCD display 21 programs

Design & Integration Door opening: Left

Adjustable feet: 10 mm
Tumble dryer can be mounted on top of washing machine 3/4" Cold water connection Loading position: Front



Safety & Mainten

Waterproof bottom plate Maximized water inlet time PEX inlet hose Anti block drain pump Overflow protection
Emergency door opening key Lockable control panel Possible to open door from inside Unbalance detection
Draining capacity: 20 l/min Overheat protection Thermal and electonic protection against overheating

Technical data

Heater capacity (W): 2000 W Drum volume: 80 I 3/4" Cold water connection Counter weight material: Cast iron Counter weight (kg): 20,1 kg Noise level: 74 dB(A)re 1 pW Noise level washing: 52 dB(A)re 1 pW Energy stars: 5 Water stars: 5 Connection rating: 2200 W Voltage: 220-240 V Number of phases: 1 Current: 10 amp Frequency: 50 Hz Net weight: 91 kg Yes

Dimensions

Product dimensions (HxWxD): 85 × 59,5 × 70 cm Adjustable feet: 10 mm Depth with door open: 1057 mm Length electrical cord: 2,3 m Lenght inlet hose: 150 cm Length outlet hose: 160 cm

Dimensions of packed product (HxWxD); 92 × 64 × 77.6 cm Gross weight: 94,4 kg Product code: 592078 EAN code: 3838782021602