



DV461110

Vacuating drawer 400 series
60 x 14 cm, Stainless steel behind glass
DV461110

- 99% vacuuming inside the chamber
 - 3 vacuuming levels for vacuuming in the chamber, max. 99%
 - 3 vacuuming levels for vacuuming outside the chamber, max. 90%
 - Hygienic stainless steel vacuuming chamber, applicable height up to 80 mm
- 3 vacuuming levels for vacuuming in the chamber, max. 99%
- 3 vacuuming levels for vacuuming outside the chamber, max. 90%
- Automatic connection recognition for vacuuming outside the chamber
- Handleless drawer
- Cushioned closing system

Application

Vacuating for sous-vide cooking.
Vacuating for fast marinating and flavouring.
Vacuating for extended storage.
Vacuating of vacuuming containers outside the chamber.
Vacuating of liquids in bottles outside the chamber.

Handling

Touch key operation.
Recessed grip at the front bottom of the drawer.

Features

Net volume 7 litres.
Capacity load max. 10 kg.
Maximum size of vacuuming bags W 240 mm x L 350 mm.
3 heat-sealing levels for different strengths of bag material.
Sealing bar, non-stick coating, removable.
Safety glass cover, opens automatically after vacuuming.
Raised vacuuming platform, 44 mm, deployable.
Utility space in vacuuming chamber, W 210 mm x L 275 mm.
Membrane for avoiding reflow of liquids during vacuuming outside the chamber.
Drying program for vacuuming pump.
Warning function.

Planning notes

The panel surface of the appliance extends 47 mm from the furniture cavity.
Installation of BS/BM/CM directly above DV in 59 cm niche without intermediate floor.
Built-in under worktop or in single niche.
The socket can be planned behind the appliance.

Connection

Total connected load 0.32 KW.
Connection cable 1.5 m, detachable.

Side view of DV 461 below BS, BM, CM

