



Color Variants

CM470111
Stainless steel-backed full glass door
Width 60 cm

Included accessories

1 x assembly screws.
1 x scoop.
1 x test strip.
1 x milk container (insulated).
1 x connection hose for milk frother.
1 x milk pipe.

CM470111

Fully automatic espresso machine 400 series

Stainless steel-backed full glass door

Width 60 cm

Controls at the top

Handleless door / automatic door opening
Fixed inlet and outlet water connection
Continuous flow heater means no waiting time and constant brewing temperature
Aroma brewing technology for a full aroma
Single portion cleaning
TFT touch display
Panel-free appliance with surface control module
One-touch operation
Personalisation function
7 light settings
Electronic fill level control for milk, water and coffee to ensure a perfect result

Type of beverage

Ristretto / 2 x Ristretto.
Espresso / 2 x Espresso.
Espresso Macchiato / 2 x Espresso Macchiato.
Coffee / 2 x Coffee.
Americano / 2 x Americano.
Caffe Latte / 2 x Caffe Latte.
Latte Macchiato / 2 x Latte Macchiato.
Cappuccino / 2 x Cappuccino.
Flat White / 2 x Flat White.
Milk froth / 2 x Milk froth.
Warm milk / 2 x Warm milk.
Hot water / 2 x Hot water.

Handling

Automatic door opening.
Rotary knob and TFT touch display operation.
Clear text display in multiple languages.
Personalisation function, option to save 8 individualised beverages.
4 beverage size settings, volume can be individually adjusted to match the size of the cup.
8 coffee strength levels from very mild to extra strong.
3 coffee temperature levels.
10 hot water temperature levels.
4 coffee-milk ratio levels.
Adjustable grinding level.
Height-adjustable coffee dispenser 7 cm to 15 cm.
Easy access to water tank, milk and coffee bean container behind the door.

Features

Maintenance-free grinding unit with ceramic discs.
Separate drawer for second ground coffee type.
Water pump with 19 bar pressure.
Double grinding and brewing cycles for extra intensity for single beverage order.
For double beverage order, two grinding and brewing cycles.
Beverage dispenser with integrated milk system.
Insulated stainless steel milk container for up to 0.5 litres.
Integrated lighting with LEDs.
Removable bean container with aroma protecting lid for 500 g allows for an effortless exchange of different types of coffee beans.
Automatic adjustment of ground coffee quantity.
Removable 2.4 litre water tank.

Characteristics

Built-in / Free-standing

Built-in

Frothing nozzle

No

Display

No

Water protection system

No

Portion sizes

All cups

Dimensions of the product (mm)

455 x 590 x 537

Dimensions of the packed product

(HxWxD) (mm)

545 x 475 x 670

Required niche size for installation

(HxWxD)

449 x 558 x 347

EAN code

4242006263812

Consumption and connection features

Electrical connection rating (W)

1600

Current (A)

10

Voltage (V)

220-240

Frequency (Hz)

50/60

Plug type

Gardy plug w/ earthing

2020-01-10

Page 1

Electronic water filter exchange

indicator.

Fresh water function to refill the water tank with fresh water.

Electronic fill level control for drip tray and container for coffee residue.

Safety

Child lock.

Aqua stop.

Cleaning

Fully automatic rinse program when machine is turned on/off.

Automatic steam cleaning of the milk system after every beverage.

Automatic cleaning and descaling program.

Emptying program to prepare the appliance for holiday or transportation.

Empty grinding function to remove coffee residues from the system when switching bean types.

Removable brewing unit.

Dishwasher-safe coffee residue

container and drip tray.

Dishwasher-safe beverage dispenser.

Planning notes

Ideal installation height 95 cm to 145 cm (top edge of niche bottom).

The door panel surface of the appliance extends 47 mm from the furniture cavity.

When installing in a corner a side clearance is required.

Door opening angle appr. 110°

(delivery status) - mounting distance to the wall has to be at least 350 mm.

Door opening angle appr. 155° -

mounting distance to the wall has to be at least 650 mm.

Door opening angle appr. 92° -

mounting distance to the wall has to be at least 100 mm (spare part No.

00636455).

Installation directly above 14 cm high warming drawer in 59 cm standardised niche.

At no point may the outlet hose be positioned higher than the bottom edge of the appliance. The outlet hose must also be at least 150 mm lower than the appliance outlet (see drawing "drainage connection").

If the appliance is placed too far from the main siphon, the drain system has to be adjusted on-site (building installation).

The water connection (1) for the inlet hose must always be accessible and not located directly behind the appliance.

The connection of the outlet hose to the siphon (2) must not be directly behind the appliance and should be accessible.

Special accessories (order as spare parts):

Part No. 17000705 Water filter

Part No. 00311819 Descaling tablets

Part No. 00311769 Cleaning tablets

Part No. 00636455 Door hinge restrictor (92° opening angle)

Part No. 11015223 Bean container with lid

Connection

Total connected load 1.6 kW.

Connection cable 1.7 m, pluggable.

Only cold water connection.

Inlet hose 165 cm with 3/4" (26.4 mm) connection, extendable.

Outlet hose (ø 18 mm) 170 cm (HT-Hose).

GAGGENAU