



EB 333 110
Stainless steel
Width 90 cm

Included in the price

- 1 enamel baking traysuit, pyrolytic clean
- 1 rotary spit
- 1 grill shelf
- 1 grill tub with grid
- 1 pluggable meat probe

Special accessories

BA 090 100
Black rotary knobs for EB 333, set of 2.

BA 018 105
Pull-out system
Fully extendable telescopic rails and enamelled cast iron frame.

BA 058 115
Heating element for baking stone and Gastronorm roaster.

BA 058 133
Baking stone.
Incl. baking stone support and pizza paddle (heating element must be ordered separately).
Not in combination with pull-out system.

GN 340 230
Gastronorm roaster in cast aluminium.
GN 2/3, height 165 mm, non-stick.

Oven EB 333

- One-piece front-hinged door with 3 mm precision crafted stainless steel front door panel
- Cushioned door opening and closing system
- Diagonally positioned light sources for optimal interior lighting
- Pyrolytic system
- 17 heating methods, with core temperature probe, rotisserie spit and baking stone function
- Hot air fan rotates in both directions for ideal heat distribution
- TFT touch display
- Panel-free appliance with control module behind glass
- Electronic temperature control from 50 °C to 300 °C
- 83 litres net volume

Heating methods

Hot air.
Eco hot air.
Top + bottom heat.
Top + 1/3 bottom heat.
Top heat.
1/3 top + bottom heat.
Bottom heat.
Hot air + bottom heat.
Hot air + 1/3 bottom heat.
Full surface grill + circulated air.
Full surface grill.
Compact grill.
Baking stone function.
Roaster function.
Dough proofing.
Defrosting.
Keeping warm.

Handling

Rotary knob and TFT touch display operation.
Clear text display in 25 languages.
Option to save individual recipes (incl. core temperature probe).
Information key with use indicators.
Front-hinged door with 90° door opening angle.

Features

Core temperature probe with automatic shut-off.
Rotisserie spit.
Baking stone socket.
Actual temperature display.
Rapid heating.
Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer.
60 W halogen light on the top.
2 x 10 W halogen light on the side.
Enamelled side shelf supports with 3 tray levels, pyrolysis-safe.

Safety

Thermally insulated door with quintuple glazing.
Child lock.
Safety shut-off.
Cooled housing with temperature protection.

Cleaning

Pyrolytic system.
Gaggenau enamel.
Heated air cleaning catalyser.

Planning notes

The door panel surface of the appliance extends 40 mm from the furniture cavity.
The outer edge of the door handle extends 90 mm from the furniture cavity.
For installation underneath cooktops: Distance between the underside of the cooktop and the top edge of the oven cavity: min. 15mm.
The planning notes for the cooktops (particularly regarding ventilation, gas/ electric connection) must be taken into account.
To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the corner of the housing.
The mains socket needs to be planned outside the built-in niche.

Connection

Total connected load 5.4 kW.
Plan a connection cable.

