

**Series 2, Slideout rangehood, 60 cm,
Silver metallic
DFM064W55A**

DWZ1IT1B4 Clean Air Standard odor filter (repl.)
DWZ1IT1I4 Clean Air Standard recirculation kit

**Slideout rangehood: built-in design that
integrates with kitchen cabinetry for a
clean finish.**

- **Three power levels:** flexible extraction to suit everyday cooking.
- **Metal grease filters:** easy to clean, dishwasher safe design for fresher kitchen air.
- **LED lighting:** energy-efficient, bright, even cooktop illumination.

Typology: Pull-out
Length electrical supply cord: 175 cm
Required niche size for installation (HxWxD): ... 162mm x 526.0mm x 290mm mm
Minimum distance above an electric cooktop: 600 mm
Minimum distance above a gas cooktop: 650 mm
Net weight: 8.8 kg
Type of control: mechanical
Number of power settings: 3
Max. air extraction: 394 m³/h
Max. air recirculation: 238 m³/h
Number of lights: 2
Noise level: 68 dB(A) re 1pW
Diameter of air outlet: 150 mm
Grease filter material: Washable aluminium
EAN code: 4242005538102
Connection rating: 108 W
Fuse protection: 10 A
Voltage: 220-240 V
Frequency: 50 Hz
Plug type: AU plug
Installation type: Built-in



Series 2, Slideout rangehood, 60 cm, Silver metallic DFM064W55A

Slideout rangehood: built-in design that integrates with kitchen cabinetry for a clean finish.

Design:

- Install into a 60cm wide upper kitchen cabinet
- Suitable for ducted or recirculated extraction
- Appliance colour: metallic silver

Features:

- 2 x LED Lights
- Colour Temperature: 3500 K
- Light Intensity: 131 lux
- 2 metal grease filter(s)

Comfort Features:

- Rocker switch control for power and light
- 3 power settings

Cleaning Comfort:

- Metal grease filter dishwasher-safe

Performance Exhaust:

- According to EN 61591 and EN/ IEC 60704-2-13 your appliance can achieve the following values in exhaust mode:
- Speed 1: extraction rate 276 m³/h; noise level 61 dB(A) re1pW
- Speed 2: extraction rate 336 m³/h; noise level 65 dB(A) re1pW
- Speed 3: extraction rate 394 m³/h; noise level 68 dB (A) re1pW

Performance Recirculation:

- Accessory required for recirculated extraction: Recirculating kit
- According to EN 61591 and EN/ IEC 60704-2-13 your appliance can achieve the following values in recirculation mode with standard recirculation kit (available as optional accessory):
- Speed 1: extraction rate 190 m³/h; noise level 66 dB(A) re1pW
- Speed 2: extraction rate 220 m³/h; noise level 69 dB(A) re1pW)
- Speed 3: extraction rate 238 m³/h ; noise level 71 dB (A) re1pW)

Technical Information:

- Power rating: 108 W
- Voltage: 220 - 240 V
- Made in Germany: produced at a CO₂ neutral production site

Planning and Installation Information:

- Appliance dimensions (HxWxD): 203 x 598 x 290 mm
- Installation dimensions (HxWxD): 162 x 526 x 290 mm
- Electrical cable length 1.75 m
- Diameter pipe Ø 150 mm



**Series 2, Slideout rangehood, 60 cm,
Silver metallic
DFM064W55A**
