

V-ZUG Australia Pty. Ltd  
2/796 High Street East Kew Vic 3102, VICTORIA/Australia  
Phone +61 (03) 9832 7500  
enquire.au@vzug.com, www.vzug.com

## Brochure DW Premira



### Selected appliance

- Article no.: 6200465003 + H42601 + H42608 + H42605
- EAN code
- Short designation: DWPQG9c
- Standard width: 90.0 cm
- Extracted air
- Front design: Stainless steel
- Installation method: Wall hood

### Also available with/as (\*)

- recirculation air Yes
- Recirculation air filter Charcoal filter (5 kg), Charcoal filter (2,5 kg)

(\*) Not all combinations are available. Ask your retailer for advice.

## Details DWPQG9c

### Design

- Standard width: 90.0 cm
- Extracted air
- Front design: Stainless steel
- Installation method: Wall hood

### Dimensions

- Appliance height: 475.0 mm
- Max. appliance height: 675.0 mm
- Front height: 55.0 mm
- Height: Extracted air/recirculation air: 5.5 cm
- Appliance width: 898.0 mm
- Appliance depth: 550.0 mm
- Max. appliance depth: 550.0 mm
- Empty weight: 25.5 kg

### Display and operation

- Controls: TouchControl
- Fan power level display
- Lighting: LED
- Number of lights: 4
- Grease filter cleaning indicator

### Energy

- Energy efficiency rating: A
- Annual energy consumption: 39.0 kWh
- Lighting efficiency rating: A
- Fluid dynamic efficiency: 30.9
- Fluid dynamic efficiency rating: A
- Type of connection: 220-240V~
- Nominal lighting output (quantity x W): 2 x 2.2 W
- Frequency (1): 50 Hz
- Connected loads: 0.13440000000000002 kW
- Fuse protection: 10.0 A
- Plug type: AS/NZS\_3112
- Connection cable: 1.5 m

### Range hood features

- Telescopic casing: Standard
- Power levels: 3 + i
- Remote control: optional
- Fleece grease filter: 3
- Side exhaust
- Non-return flap, integrated/attached: included

### Functions

- Intensive setting
- Automatic after-running time

### Additional data

- Exhaust air connection (diameter): 150.0 mm
- Lighting efficiency: 62.7
- Illumination on cooking surface: 276.0 lux
- Grease absorption capacity rating: C
- Extracted air output, intensive setting: 679 m<sup>3</sup>/h
- Extracted air output, max. setting: 423 m<sup>3</sup>/h
- Extracted air output, min. setting: 255 m<sup>3</sup>/h
- Extracted air noise output, intensive setting: 62.0 dB(A)
- Extracted air noise level, max. setting: 51.0 dB(A)
- Extracted air noise output, min. setting: 39.0 dB(A)
- Recirculation air output, intensive setting: 556 m<sup>3</sup>/h
- Recirculation air output, max. setting: 358 m<sup>3</sup>/h
- Recirculation air output, min. setting: 222 m<sup>3</sup>/h
- Motor(s): 1
- Motor output: 130 W
- Feature level: 5

### Service and interfaces

- Warranty: 2 years