



AR401142

AA400510:
Window contact switch with cable

AD702052:
Exhaust air pipe dia. 200mm

Remote fan unit 400 series

AR401142

- Efficient BLDC technology
 - Powerful remote fan unit to combine with motorless appliances
 - Air output according to EN 61591 Max. extraction rate: 855 m³/h
 - Sound power level depends on the built-in situation.
 - 3 electronically controlled power levels and one intensive mode.
 - Efficient BLDC technology
- Powerful remote fan unit to combine with motorless appliances

Output

Air output according to EN 61591 Max. extraction rate: 855 m³/h

Sound power level depends on the built-in situation.

Features

3 electronically controlled power levels and one intensive mode.

Fan technology with highly efficient, brushless DC motor (BLDC).

Including sound insulation to minimise the noise level.

Stainless steel housing.

Pipe connection pieces on intake side: 1x DN 200 round.

Retaining bracket for installation on an outside wall enclosed.

Planning notes

Connection to the respective appliances via network cable.

Installation in an exterior area allows for a reduced noise level in the kitchen

Installation on an outside wall.

Control box must be installed indoors.

Acceptable temperature range for installation of the control box: -25 to 60 °C.

Distance for free air space from ground (or other object) to center of the pipe: min 60 cm

When installing a ventilation hood with air extraction mode and a chimney-vented fireplace, the power supply line of the ventilation appliance needs a suitable safety switch.

Connection

Total connected load 180 W.

Connecting cable 1.8 m, pluggable.

Network cable 5 m.

