

V-ZUG Australia Pty. Ltd
2/796 High Street East Kew Vic 3102, VICTORIA/Australia
Phone +61 (03) 9832 7500
enquire.au@vzug.com, www.vzug.com

Brochure DI-Premira



Selected appliance

- Article no.: 6300465003 + H42598 + H42608
- EAN code
- Short designation: DIPQG10c
- Standard width: 100.0 cm
- Extracted air
- Front design: Stainless steel
- Installation method: Island hood

Also available with/as (*)

- recirculation air Yes
- Recirculation air filter Chargoal filter (5 kg), Chargoal filter (2,5 kg)

(*) Not all combinations are available. Ask your retailer for advice.

Details DIPQG10c

Design

- Standard width: 100.0 cm
- Extracted air
- Front design: Stainless steel
- Installation method: Island hood

Dimensions

- Appliance height: 490.0 mm
- Max. appliance height: 685.0 mm
- Front height: 70.0 mm
- Height: Extracted air/recirculation air: 7.000000000000001 cm
- Appliance width: 1000.0 mm
- Appliance depth: 700.0 mm
- Max. appliance depth: 700.0 mm
- Empty weight: 34.0 kg

Display and operation

- Controls: TouchControl
- Fan power level display
- Lighting: LED
- Number of lights: 4
- Grease filter cleaning indicator

Energy

- Energy efficiency rating: A
- Annual energy consumption: 42.3 kWh
- Lighting efficiency rating: A
- Fluid dynamic efficiency: 30.9
- Fluid dynamic efficiency rating: A
- Type of connection: 220-240V~
- Nominal lighting output (quantity x W): 4 x 2.2 W
- Frequency (1): 50/60 Hz
- Connected loads: 0.1388 kW
- Fuse protection: 10.0 A
- Plug type: AS/NZS_3112
- Connection cable: 1.5 m

Range hood features

- Telescopic casing: Standard
- Power levels: 3 + i
- Remote control: optional
- Fleece grease filter: 3
- Non-return flap, integrated/attached: included

Functions

- Intensive setting
- Automatic after-running time

Additional data

- Exhaust air connection (diameter): 150.0 mm
- Lighting efficiency: 56.8
- Illumination on cooking surface: 500.0 lux
- Grease absorption capacity rating: C
- Extracted air output, intensive setting: 679 m³/h
- Extracted air output, max. setting: 423 m³/h
- Extracted air output, min. setting: 255 m³/h
- Extracted air noise output, intensive setting: 62.0 dB(A)
- Extracted air noise level, max. setting: 51.0 dB(A)
- Extracted air noise output, min. setting: 39.0 dB(A)
- Recirculation air output, intensive setting: 558 m³/h
- Recirculation air output, max. setting: 353 m³/h
- Recirculation air output, min. setting: 224 m³/h
- Motor(s): 1
- Motor output: 130 W
- Feature level: 4

Service and interfaces

- Warranty: 2 years