

iQ700
LC91BUV50A
90 cm Wall Mounted Canopy
Ranghood



The wall hood convinces with a very high extraction rate in a distinguished design that perfectly matches your kitchen.

- ✓ Touch Control – thanks to the integrated flat surface control panel, adjustments can be easily made with just one finger
- ✓ Impressive extraction rate (964 m³/h) for efficient odour and steam removal.
- ✓ The power level of your hood can be adjusted by your cooktop
- ✓ The hood adapts the level of steam automatically matching the amount of steam and odours.
- ✓ LED light: Optimal visibility and atmosphere when cooking.
- ✓ Extremely quiet when being used (64 db(A)).

Features

Technical Data

Color chimney : Stainless steel
Typology : Chimney
Approval certificates : Australia Standards, VDE
Length electrical supply cord (cm) : 130
Height of product, without chimney (mm) : 46
Minimum distance above an electric hob : 550
Minimum distance above a gas hob : 650
Net weight (kg) : 21.201
Type of control : Electronic
Number of speed settings : 3-stage + 2 intensive
Maximum output air extraction (m³/h) : 602
Boost position output recirculating (m³/h) : 428
Maximum output recirculating air (m³/h) : 362
Boost position air extraction (m³/h) : 964
Number of lights : 3
Noise level (dB) : 64
Diameter of air outlet (mm) : 120 / 150
Grease filter material : Washable stainless steel
EAN code : 4242003835326
Connection Rating (W) : 269
Current (A) : 10
Voltage (V) : 220-240
Frequency (Hz) : 50; 60
Plug type : AU plug
Installation typology : Wall-mounted

Optional accessories

LZ57300	cleanAir Recirculation Kit
LZ56200	CleanAir active carbon filter spare part
LZ53451	Active carbon filter
LZ53450	Recirculating kit



iQ700
LC91BUV50A
90 cm Wall Mounted Canopy
Rangehood

Features

Design & Innovation

- Box brand design
- Suitable for ducted and re-circulating operation
- Accessories required for recirculation mode: CleanAir Module
- 3 x 3W LED lights

Convenience

- Wall mounted rangehood
- softLight with dimming function
- lightControl white LED control panel
- Boost function
- climateControl sensor automatically adjusts the rangehood power level to the steam and odours
- Saturation display for filters
- Dishwasher safe metal grease filters
- Stainless steel filter covers, dishwasher safe

Power and Mode of Operation

- Extraction rate according to EN 61591 ø 15 cm:
- max. Normal use 601 m³/h
- Intensive 964 m³/h
- Extraction rate in recirculation mode:
- Max. normal use: 362 m³/h
- Intensive: 428 m³/h
- 3 power levels + 2 intensive levels
- Intensive operation automatic revert - 6min
- Automatic run on for Automatic run on - 10 min
- Noise min./max. Normal Level: 45/64 dB
- Noise max. Intensive setting: 73 dB
- Efficient BLDC technology
- cooktop-based hood control
- (with matching cooktop)
- Sound insulation mats for optimised sound absorption
- with one-way flap

Technical Information

- wall fixing system
- Dimensions exhaust air (HxWxD): 628-954 x 898 x 500 mm
- Dimensions recirculating (HxWxD): 628-1064 x 898 x 500 mm
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Power rating: 269 W
- Electrical cable length 1.3 m
- Voltage: 220 - 240 V
- Energy Efficiency Class: A+ (at a range of energy efficiency classes from A++ to E)

Dimensioned drawings

