



Color Variants

|                                    |
|------------------------------------|
| WSP222100                          |
| Glass front in Gaggenau Anthracite |
| Width 60 cm, Height 29 cm          |
| WSP222110                          |
| Glass front in Gaggenau Metallic   |
| Width 60 cm, Height 29 cm          |
| WSP222130                          |
| Glass front in Gaggenau Silver     |
| Width 60 cm, Height 29 cm          |

|                                    |
|------------------------------------|
| WSP222100                          |
| Warming drawer 200 series          |
| Glass front in Gaggenau Anthracite |
| Width 60 cm, Height 29 cm          |

Flush installation  
Handleless drawer  
Push-to-open system  
Hygienic stainless steel interior with glass bottom  
4 power levels in the temperature range 40 °C to 80 °C (glass surface)  
Also for preparing and cooking meals, and for keeping meals warm

**Heating methods**  
Defrosting of meals/proving of yeast dough.  
Preheating of small beverage containers.  
Keeping meals warm/slow cooking meals.  
Warming ovenware.

**Handling**  
Rotary knob operation.

**Features**  
Net volume 52 litres.  
Volume capacity: Dinner service for 12 people including ø 24 cm plates and soup bowls, additional bowls and a serving dish depending on size.  
Max. load 25 kg.  
Usable interior dimensions  
W 468 x H 242 x D 458 mm.  
Heating under glass bottom for easy cleaning.  
Fan for even heat distribution for fast warming ovenware.  
Status display, visible in the glass front.  
Glass bottom made of safety glass.

**Planning notes**  
Necessary lateral gap between appliance front and furniture panel of min. 5 mm.  
The door panel surface of the appliance extends 21 mm from the furniture cavity.  
The socket can be planned behind the appliance.

**Connection**  
Total connected load 0.81 kW.  
Connection cable 1.5 m, pluggable.

|                                                |
|------------------------------------------------|
| Characteristics                                |
| Built-in / Free-standing                       |
| Built-in                                       |
| Color / Material Front                         |
| Anthracite                                     |
| Maximum number of plates                       |
| 40                                             |
| Maximum number of espresso cups                |
| 120                                            |
| Dimensions of the product (mm)                 |
| 288 x 590 x 548                                |
| Dimensions of the packed product (HxWxD) (mm)  |
| 210 x 660 x 660                                |
| Required niche size for installation (HxWxD)   |
| 288 x 560 x 550                                |
| Power output heating                           |
| 0.810                                          |
| Power Level                                    |
| high, low, medium, plate                       |
| Type of control setting and signalling devices |
| Rotary knob                                    |
| Temperature control                            |
| electronic                                     |
| Time control                                   |
| No                                             |

|                                                  |
|--------------------------------------------------|
| Consumption and connection features              |
| Electrical connection rating (W)                 |
| 810                                              |
| Current (A)                                      |
| 10                                               |
| Voltage (V)                                      |
| 220-240                                          |
| Frequency (Hz)                                   |
| 50; 60                                           |
| Plug type                                        |
| Gardy plug w/ earthing                           |
| Universal Product Code                           |
| 825225916369                                     |
| Color / Material Front                           |
| Anthracite                                       |
| Alternative colors available                     |
| WSP222110, WSP222130                             |
| Approval certificates                            |
| CE, VDE                                          |
| Length of electrical supply cord (in)            |
| 71 "                                             |
| Required cutout/niche size for installation (in) |
| x x                                              |
| Appliance Dimensions (h x w x d) (in)            |
| x x                                              |
| Dimensions of the packed product (in)            |
| 8.26 x 25.98 x 25.98                             |
| Net weight (lbs)                                 |
| 46                                               |
| Gross weight (lbs)                               |
| 50                                               |
| Length electrical supply cord (cm)               |
| 150                                              |
| Required niche size for installation (HxWxD)     |
| 288 x 560 x 550                                  |
| Dimensions of the product (mm)                   |
| 288 x 590 x 548                                  |
| Dimensions of the packed product (HxWxD) (mm)    |
| 210 x 660 x 660                                  |
| Net weight (kg)                                  |
| 21.0                                             |
| Gross weight (kg)                                |
| 23.0                                             |
| 2018-02-13                                       |
| Page 1                                           |

