


N 90 T56TS31NO FLEXINDUCTION COOKTOP WITH TWISTPAD® FIRE CONTROL







## Optional accessories

Z9410X1	Stainless Steel roaster with glas lid
Z9415X1	Steaming Rack for Stainless Steel roaste
Z9416X2	Griddle Plate
Z9417X2	Teppan Yaki (large)
Z9442X0	Set of 3 pots and 1 pan
Z9453X0	System pan diameter 21cm

## Standalone FlexInduction cooktop with TwistPad® Fire control.

- $\sqrt{\phantom{a}}$  Induction With induction cooking, the heat is generated directly in the cookware for precise cooking that stops when power is off.
- $\sqrt{\ }$  FlexInduction The FlexZone lets you place your pots and pans anywhere you want and heats them exactly where they stand.
- $\sqrt{\ }$  The TwistPad® Fire is a removable, magnetic, illuminated control knob that gives you precise, convenient control over all cooking zones. And to make things even easier, only the selectable functions are illuminated.
- $\sqrt{\ }$  PowerMove The FlexZone is divided into three heating zones: boiling in front, simmering in the middle and warming in the rear.
- $\sqrt{\mbox{ FryingSensor}}$  The FryingSensor with 5 selectable temperature settings monitors the set temperature and holds it steady. So there's no more burning.
- $\sqrt{}$  Stainless-steel flush-fitted trim

#### Features

#### Technical Data

Product name/family: Cooking zone ceramic

Construction type: Built-in Energy input : Electric

Total number of positions that can be used at the same time: 3 Required niche size for installation (HxWxD): 51 x 560-560 x

490-500

Width of the product (mm): 606

Dimensions of the product (mm) :  $51 \times 606 \times 546$ 

Dimensions of the packed product (HxWxD) (mm) :  $126 \times 753 \times 603$ 

Net weight (kg): 13.7 Gross weight (kg): 15.0 Residual heat indicator : Separate Location of control panel: Hob front Basic surface material: Ceramic Color of surface: Black, Stainless steel Color of frame: Stainless steel Approval certificates: AENOR, CE Length electrical supply cord (cm): 110 EAN code: 4242004191797

Electrical connection rating (W): 7400 Voltage (V): 220-240

Frequency (Hz): 50; 60



# N 90 T56TS31N0 FLEXINDUCTION COOKTOP WITH TWISTPAD® FIRE CONTROL

#### Features

#### Handling

• TwistPad® Fire

### Flexibility

- 3 induction zones
- Cooking zones:

 $1\times\varnothing$  280 mm, 2.6 KW (max. Power level 3.7 KW) Induction;  $1\times\varnothing$  380 mmx210 mm, 3.3 KW (max. Power level 3.7 KW) Induction or  $2\times\varnothing$  190 mm, 2.2 KW (max. Power level 3.7 KW) Induction

### Comfort & Convenience

- PotBoost function for all cooking zones
- PanBoost
- PowerMove
- FryingSensor with 5 temperature settings
- 17 power levels for each cooking zone
- Residual heat indicator: Digital 2-step
- LED display and timer with auto switch off for all cooking zones,
  Alarm clock, Count-up timer
- Automatic pan recognition sensor Power management function Automatic safety switch-off Child safety lock Wipe protection function
- ReStart function
- QuickStart Quick and automatic first pot detection
- Keep warm function for all cooking zones
- Energy consumption display

#### Design

• Black ceramic glass with stainless steel flush-fitted trim

#### **Technical Information**

- 60 cm width
- Installation measurements: 560 mm x 490 mm
- Length wire connection: 110 cmMin. worktop thickness: 30 mm
- 7.4 kW total connected load
- Voltage: 220 240 V
- Cable included

N 90 T56TS31N0 FLEXINDUCTION COOKTOP WITH TWISTPAD® FIRE CONTROL

# Dimensioned drawings

