

iQ700
LI97SA680A
90 cm Slideout Rangehood
Appliance colour: Stainless steel



Optional accessories

LZ49200	Installation kit for 90cm wide wall unit
LZ46810	CleanAir active carbon filter
LZ46800	CleanAir Recirculation Kit

The powerful slideout rangehood practically disappears into the upper cabinet.

- ✓ The energy saving LED lighting with dimmer function ensures ambient lighting and optimal visibility when cooking.
- ✓ The highly efficient 700 m³/h extraction rate provides ideal air quality in the kitchen.
- ✓ 49 dB at level 2 (310 m³/h) - 150mm ducted.
- ✓ The intensive setting temporarily increases the extraction rate when kitchen vapour is especially intense, with automatic revert to previous setting after 6 min.

Features

Technical Data

Typology : Pull-out
Approval certificates : Australia Standards, VDE
Length electrical supply cord (cm) : 175
Required niche size for installation (HxWxD) : 385mm x 524mm x 290mm
Minimum distance above an electric hob : 430
Minimum distance above a gas hob : 650
Net weight (kg) : 14.203
Type of control : Electronic
Number of speed settings : 3-stage + 2 intensive
Maximum output air extraction (m³/h) : 400
Boost position output recirculating (m³/h) : 480
Maximum output recirculating air (m³/h) : 290
Boost position air extraction (m³/h) : 700
Number of lights : 2
Noise level (dB) : 54
Diameter of air outlet (mm) : 150 / 120
Grease filter material : Washable stainless steel
EAN code : 4242003723524
Connection Rating (W) : 146
Current (A) : 10
Voltage (V) : 220-240
Frequency (Hz) : 60; 50
Plug type : AU plug
Installation typology : Built-in



iQ700**LI97SA680A****90 cm Slideout Rangehood****Appliance colour: Stainless steel****Features****Design & Innovation**

- Telescopic comfort installation
- Black profile handle included
- 2 x 3 Watt LED Lights
- softLight with dimming function

Convenience

- For installation into a 60 cm or 90 cm wide cupboard
- 3 power levels + 2 intensive levels
- Electronic controls with touchControl, Automatic function
- climateControl sensor automatically adjusts the rangehood power level to the steam and odours

Power and Mode of Operation

- Extraction rate according to EN 61591 ø 15 cm:
- max. Normal use 400 m³/h
- Intensive 700 m³/h
- Suitable for ducted and re-circulating operation
- Accessories required for recirculation mode: CleanAir Module
- 2 single inlet vertical fans, Efficient BLDC technology
- Intensive operation automatic revert - 6min
- Automatic run on for Automatic run on - 10 min
- Boost function

Cleaning

- Dishwasher safe metal grease filters
- Stainless steel filter covers, dishwasher safe
- Saturation display for filters
- Safety and Quality
- Noise level according to EN 60704-3 und EN 60704-2-13 exhaust air:
- Max. normal use: 54 dB(A) re 1 pW (40 dB(A) re 20 µPa sound pressure)
- Intensive: 66 dB(A) re 1 pW (52 dB(A) re 20 µPa sound pressure)
- Sound insulation mats for optimised sound absorption
- 5 year warranty
- Dimensions (HxWxD)
- Power rating: 146 W
- Appliance dimensions (HxWxD): 426 x 898 x 290 mm
- Built-in dimensions (HxWxD): 385 x 524 x 290 mm
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)

Appliance colour: Stainless steel

measurements in mm

measurements in mm

measurements in mm

measurements in mm

measurements in mm

measurements in mm

iQ700

LI97SA680A

90 cm Slideout Rangehood

Appliance colour: Stainless steel

Dimensioned drawings

