

PFD 103 SCi XXL

Integrated XXL dishwasher with 3D MultiFlex cutlery tray for easily managing piles of domestic dishes.



- Wash performance: 15 place settings in just 36min.*
- Flexible loading of load items for the best cleaning results
- Perfect lighting for easy loading BrilliantLight
- Everything completely dryAutoOpen assisted drying
- Innovative design and maximum convenience 3D MultiFlex tray

EAN: 4002516446118 / Article no.: 61010314AUS / Mat. no.: 11807780

Construction type and version	
Construction type	Semi-integrated dishwasher
Range	ProfiLine
Wash system	Fresh water
Number of levels	2
Front	Without front
Side panels	Galvanised
Minimum front panel weight in kg	4
Maximum front panel weight in kg	11
Application	
Suitable for offices	•
Suitable for domestic use	•
Suitable for sports clubs	•
Performance data	
Proven hygiene	•
Circulation pump Qmax in I/min.	75
Shortest programme duration in min.	36
Maximum final rinse temperature in °C	82
Cleaning performance, place settings/cycle	15
Service life in wash cycles	12,500
Controls	
Control system	Electronic controls
Programme selection	Program Selector Buttons
Max. delay start in h	24
Max. delay start in h Time left display	<u>24</u>
Time left display	•
Time left display Programmes [number]	8
Time left display Programmes [number] Programme sequence indicator	• 8 •
Time left display Programmes [number] Programme sequence indicator Filter indicator light	• 8 •
Time left display Programmes [number] Programme sequence indicator Filter indicator light Selectable display languages	• 8 •
Time left display Programmes [number] Programme sequence indicator Filter indicator light Selectable display languages Standard electrical connection	8 • •
Time left display Programmes [number] Programme sequence indicator Filter indicator light Selectable display languages Standard electrical connection Electrical connection	8 • • • AC 230V 50HZ
Time left display Programmes [number] Programme sequence indicator Filter indicator light Selectable display languages Standard electrical connection Electrical connection Heater rating in kW	• 8 • • • • • • • • • • • • • • • • • •
Time left display Programmes [number] Programme sequence indicator Filter indicator light Selectable display languages Standard electrical connection Electrical connection Heater rating in kW Total connected load in kW	• 8 • • • • • • • • • • • • • • • • • •
Time left display Programmes [number] Programme sequence indicator Filter indicator light Selectable display languages Standard electrical connection Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A	• 8 • • • • • • • • • • • • • • • • • •
Time left display Programmes [number] Programme sequence indicator Filter indicator light Selectable display languages Standard electrical connection Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Length of mains connection cable in m	• 8 • • • • • • • • • • • • • • • • • •
Time left display Programmes [number] Programme sequence indicator Filter indicator light Selectable display languages Standard electrical connection Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Length of mains connection cable in m Provided with plug	• 8 • • • • • • • • • • • • • • • • • •
Time left display Programmes [number] Programme sequence indicator Filter indicator light Selectable display languages Standard electrical connection Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Length of mains connection cable in m Provided with plug Possible voltage variant 1	• 8 • • • • • • • • • • • • • • • • • •
Time left display Programmes [number] Programme sequence indicator Filter indicator light Selectable display languages Standard electrical connection Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Length of mains connection cable in m Provided with plug Possible voltage variant 1 Electrical connection	AC 230V 50HZ 1.90 2.10 10 1.70 3N AC 400V 50HZ



PFD 103 SCi XXL

Integrated XXL dishwasher with 3D MultiFlex cutlery tray for easily managing piles of domestic dishes.



alorioo.	
Water connection/drainage	
Cold or hot water [number]	_ <u>1 </u>
Required flow pressure in bar	0,30-10,00
Drain pump [DN]	
Maximum delivery head for drain pump in cm	100
Integrated water softener	•
Maximum water hardness in mmol/l	6.50
Water protection system	Waterproof system
Length of water inlet hose in cm	150
Length of water drain hose in cm	150
Dimensions and weight	
External dimensions, net height in mm	845
External dimensions, net width in mm	598
External dimensions, net depth in mm	570
External dimensions, gross height in mm	960
External dimensions, gross width in mm	670
External dimensions, gross depth in mm	700
Usable space in wash cabinet, height in mm	580
Usable space in wash cabinet, width in mm	510
Usable space in wash cabinet, depth of upper basket in mm	450
Usable space in wash cabinet, depth of lower basket in mm	450
In-feed height above floor in mm	210
Net weight in kg	52
Gross weight in kg	59
Maximum floor loading in N	1,000
Emissions data	1,722
Sound power (LwA) in dB(A) re 1 pW	45.0
Programmes	
Universal	•
Short	•
Hygiene	•
Cold/Pre-wash	•
Glasses	•
Plastics	•
Energy save/Eco	•
Intensive	•
Basket design	
MaxiComfort baskets	•
Flexible FlexLine basket design	•
FlexCare glass holder [number]	4
FlexCare cup rack [number]	2
Height-adjustable upper basket	•
Patented 3D MultiFlex tray	•



PFD 103 SCi XXL

Integrated XXL dishwasher with 3D MultiFlex cutlery tray for easily managing piles of domestic dishes.



Features	
Commercial-grade electrical connection	•
Drying	AutoOpen assisted drying Extra drying Active condensation drying
1 combi dispenser in the door for powder cleaning agent and rinsing agent	•
Wash cabinet made from high-quality stainless steel	•
BrilliantLight	•
AutoClose	•
EcoFeedback	•
Brilliant GlassCare	•
Safety lock	•
Adjustable final rinse temperature	•
Optical interface	•
SmartStart	•
FlexiTimer with EcoStart	•
Connection options	
External dispensing module for liquid detergent	•
Standards, test certificates and symbols	
CE	•
Complies with Machinery Directive 2006/42/EC	•
VDE	•
EMC radio suppressed	•
EN 1717	•
WaterMark	•