

## PWM 1108 SmartBiz [EL DP]

Washing machine, electrically heated

commercial quality with a programme running time of 79 min, easy installation.



- Drum volume 64 l, load capacity 8.0 kg
- High-quality stainless steel control panel, Miele honeycomb drum
- Supplied ready for connection incl. mains plug
- Professional programme running time of just 79 min with a 8.0 kg load size
- Space-saving installation as washer-dryer stack

EAN: 4002516811305 / Material number: 12507000 / Old Material Number: 51110801AUS

Construction type and design	
Construction type	Front-loader, stackable
Range	SmartBiz
Front	Lotus white
Load in kg	8.0
Drum volume in l	64
Door opening [Ø] in mm	300
Door opening angle in degrees	167
Door hinge	right
Maintenance-free synchronous motor	•
Stainless steel honeycomb drum	•
Application	
Suitable for the hotel and catering industry	•
Suitable for small businesses	•
Suitable for universities, nurseries and schools	•
Suitable for sports clubs	•
Suitable for beauty salons, spas and fitness centres	•
Suitable for domestic use	•
Performance data	
Tested virucidal efficacy	•
Specific water consumption for cold water connection in l/kg	6.50
Specific energy consumption for cold water connection in kWh/kg	0.16
Water consumption with cold water connection in l	52.0
Energy consumption with cold water connection in kW	1.30
Programme duration in minutes with cold water connection	79
Residual moisture with cold rinse in %	49
Spin speed in rpm	1400
g-factor	535
Tested operating hours	15000
Controls	
Control system	DirectSensor 7-segment
Max. delay start in h	24
Time left display	•
Programme sequence indicator	•
Control panel with plain text	•
Dispensing	
Detergent drawer	3 compartments
Standard electrical connection	
Heating type	Electric
Electrical connection	230V~ 50HZ
Drying class in kW	2.10
Total rated load in kW	2.30
Fuse rating in A	10
Provided with plug	•
Water connection/drainage	
Cold water [number]	1x 1/2" hose w/ 3/4" th. union
Drain pump	DN 22

## PWM 1108 SmartBiz [EL DP]

Washing machine, electrically heated

commercial quality with a programme running time of 79 min, easy installation.



EAN: 4002516811305 / Material number: 12507000 / Old Material Number: 51110801AUS

### Dimensions and weight

External dimensions, height in mm	850
External dimensions, width in mm	596
External dimensions, depth in mm	636
External dimensions, gross height in mm	944
External dimensions, gross width in mm	660
External dimensions, gross depth in mm	690
Net weight in kg	91.0
Gross weight in kg	95
Maximum floor load in N	2820

### Emissions data

Emission sound pressure level in the workplace	<70 dB(A) re 20 µPa
Heat dissipation into the room in MJ/h	1.00

### Features

Hard-wearing stainless-steel flange	•
Special heater element	•
Automatic load control	•
Machine-independent accessories	•

### Efficiency and sustainability

Recycling rate in %	95
---------------------	----

### Connection options

Optical interface for service access	•
WiFiConn@ct	•

### Standards, certs, symbols

Splash-proof safety rating IPX4	•
WEEE	•
Complies with Machinery Directive 2006/42/EC	•