



DWAU6315X3

Dishwashers, Universale, Under counter built-in, 60 cm, Number of place settings: 15 AU, Stainless steel



TYPE

Product Family: Dishwashers • Commercial height: 82 cm • Number of place settings: 15 AU • Installation: Under counter built-in • Commercial width: 60 cm • Kitchen panel: Not supplied • EAN code: 8017709297176

AESTHETICS

Color: Stainless steel • Finishing: Fingerproof • Aesthetics: Universale • Front panel colour: Finger friendly stainless steel • Door type: Without frame • Door colour: Finger friendly stainless steel • LED/display colour: White • Buttons colour: Silver (oropal grey)

PROGRAMS / FUNCTIONS

N. of programmes: 5+5 quick programmes • Soak: Yes • Rapid 27': Yes • Ultraclean: Yes • Regular Quick: Yes • Delicate and Quick: Yes • Daily Quick: Yes • Auto 60-70: Yes • Strong and fast: Yes • Regular: Yes • Normal ECO: Yes • Washing temperatures: 45, 50, 65, 70 °C

OPTIONS

Energysave option: Yes • Delay timer option: Up to 24 hours • 1/2 load FlexiZone option: Yes • Options for tabs FlexiTabs: Yes • Quick Time option: Yes

BASKETS

N° baskets: 3, Flexi • Basket colour: Grey • Basket components colour: Grey • Handle: In plastic with stainless steel insert on upper and lower basket • Upper Basket: With central fixed racks • Upper basket with EasyGlide System: Yes • Height adjustment of the upper basket: On three levels • Largest loadable dish in upper basket: 19,0 cm • Lower Basket: With completely foldable racks and glass holder • Lower basket with anti-drip inserts: Yes • Largest loadable dish in lower basket: 30,0 cm • Cutlery basket: 13 place settings sliding • Colour Inner Components: Blue

TECHNICAL FEATURES

Controls: Electronic • Display: Delayed start, Programme time indicator, Time to end indication • Door opening system: Yes • Display type: LED (external) • Rinse aid indicator: Light • Progress indicator: Yes • End of cycle indicator: On display, with acoustic signal • Washing system: Orbital • Drying system: Natural condenser drying, with EnerSave automatic door opening system at the end of the cycle • Motor: Single phase • Third spray arm: Single • Turbidity sensor Aquatest: Yes • Flood protection system: Total Acquastop • Water supply: Single; cold/hot water max. 60°C - energysave with hot water up to 35% • Max water hardness: 100°FH;58°dH • Steam protection: In plastic • Tub material: Stainless steel • Filter: Stainless steel • Concealed heating element: Yes • Min. and max plinth height: 100 - 170 mm • Hinges: Self balancing with fixed hinges • Adjustable feet: 7cm, from 820 to 890 mm • Adjustable plinth: By height and depth

PERFORMANCE / ENERGY LABEL

Noise level: 49 dB(A) re 1pW • Energy consumption per cycle (kWh/cycle): 0.650 kWh • Water consumption per cycle (l/cycle): 9,9 l • Annual energy consumption: 243 kWh/a • Reference programme: Normal ECO • Total cycle time of reference programme (min): 220 min • Duration of the stand by on mode (min): 5 min • Energy Label ex EU: Energy rating: 3,5 stars - Water rating: 6 stars

ELECTRICAL CONNECTION

Connected power: 1800 W • Voltage: 220-240 V • Type of connection: Single-phase • Frequency (Hz): 50 Hz • Power supply cable length: 140 cm

LOGISTIC INFORMATION

Dimensions of the product HxWxD (mm): 818x598x570

