



Color Variants

VI260114
Stainless steel control panel
Width 60 cm

Installation Accessories

VV200014
Stainless steel connection strip
for combination with further Vario
cooktops

VI260114
Vario induction cooktop 200 series
Stainless steel control panel
Width 60 cm

Can be combined with the cooktops
of the Vario 200 series to a harmonic
unity.
Generous control panel for
comfortable and secure operation.

Cooking zones

1 induction cooking zone ø 21 cm
(2200 W, with booster 3300 W).
2 induction cooking zones ø 18 cm
(1800 W, with booster 2500 W).
1 induction cooking zone ø 15 cm
(1400 W, with booster 1800 W).

Handling

Control knobs with cooking zone and
output level markings.
Electronic control in 9 output levels.

Features

Cooking zone marking.
Pot detection.
Booster function for all cooking zones
(two cooking zones - left and right -
can be operated simultaneously with
booster function).

Safety

Residual heat indication.
Operation indicator.
Safety shut-off.

Planning notes

Operates with magnetic (induction)
iron pots and pans only. For an optimal
heat distribution, the use of sandwich
bottom cookware is recommended.
Immersion depth 49 mm.
Cooktop clamping range: 20 - 40 mm.
Intermediate shelf is recommended.
Appliance must be fixed from
underneath.

Connection

Total connected load 7.4 kW.
Connecting cable 1.5 m without plug.

Characteristics

Product name/family
Cooking zone ceramic
Construction type
Built-in
Energy input
Electric
Total number of positions that can be
used at the same time
4
Type of control setting devices
Required niche size for installation
(HxWxD)
49 x 560-560 x 490-490
Width of the product (mm)
580
Dimensions of the product (mm)
49 x 580 x 523
Dimensions of the packed product
(HxWxD) (mm)
113 x 1091 x 709
Net weight (kg)
12.970
Gross weight (kg)
14.0
Residual heat indicator
Separate
Location of control panel
Hob front
Type of external control possibility
Basic surface material
Ceramic
Color of surface
Black, Stainless steel
Color of frame
Stainless steel
Approval certificates
AENOR, CE
Length of electrical supply cord (cm)
150
EAN code
4242006194611

Consumption and connection features

Electrical connection rating (W)
7400
Gas connection rating (W)
Current (A)
Voltage (V)
220-240
Frequency (Hz)
50; 60

created on 2019-02-04
Page 1

