



CMP250102

Fully automatic espresso machine 200 series
60 x 45 cm, Anthracite, Removable water tank
CMP250102

- The TFT touch display makes personalising your perfect coffee easy. Choose between 12 coffee options and make up to 15 different options by adjusting coffee strength, temperature and milk volume
- Save up to 8 individualised beverages
- Two cup brewing simultaneously
- Water, bean and milk levels
- Automatic steam cleaning of the milk system after every beverage
- Handless door / cushioned door closing system

Continuous flow heater means no waiting time and constant brewing temperature

Aroma brewing technology for a full aroma

Single portion cleaning

TFT touch display

Panel-free appliance with surface control module

One-touch operation

Personalisation function

Electronic fill level control for milk, water and coffee for a perfect result

Type of beverage

Ristretto / 2 x Ristretto.

Espresso / 2 x Espresso. Espresso Macchiato /

2 x Espresso Macchiato. Coffee / 2 x Coffee.

Americano / 2 x Americano. Caffè Latte / 2 x

Caffè Latte. Latte Macchiato / 2 x Latte

Macchiato. Cappuccino / 2 x Cappuccino. Flat

White / 2 x Flat White. Milk froth / 2 x Milk froth.

Warm milk / 2 x Warm milk. Hot water / 2 x Hot

water.

Handling

Door with cushioned door closing system.

Rotary knob and TFT touch display operation.

Clear text display.

Personalisation function, option to save 8 individualised beverages.

4 beverage size settings, volume can be individually adjusted to match the size of the cup.

8 coffee strength levels from very mild to extra strong.

3 coffee temperature levels.

10 hot water temperature levels.

4 coffee-milk ratio levels.

Adjustable grinding level.

Height-adjustable coffee dispenser 7 cm to 15 cm.

Easy access to water tank, milk and coffee bean container behind the door.

Features

Maintenance-free grinding unit with ceramic discs.

Separate drawer for second ground coffee type.

Water pump with 19 bar pressure.

Double grinding and brewing cycles for extra intensity for single beverage order.

For double beverage order, two grinding and brewing cycles.

Beverage dispenser with integrated milk system. Insulated stainless steel milk container for up to 0.5 litres.

Integrated lighting with LEDs.

7 light settings

Removable bean container with aroma protecting lid for 500 g allows for an effortless exchange of different types of coffee beans.

Automatic adjustment of ground coffee quantity.

Removable 2.4 litre water tank.

Electronic water filter exchange indicator.

Electronic fill level control for drip tray and container for coffee residue.

Home network integration for digital services (Home Connect) either via cable connection LAN (recommended) or wireless via WiFi.

The use of the Home Connect functionality depends on the Home Connect services, which are not available in every country. For further information please check: home-connect.com.

Selected digital services (Gaggeneau Home Connect)

Coffee World: extended choice of coffee specialties from all over the world.

Remote control and monitoring.

Safety

Child lock.

Cleaning

Fully automatic rinse program when machine is turned on/off.

Automatic steam cleaning of the milk system after every beverage.

Automatic cleaning and descaling program.

Emptying program to prepare the appliance for holiday or transportation.

Empty grinding function to remove coffee residues from the system when switching bean types.

Removable brewing unit.

Dishwasher-safe coffee residue container and drip tray.

Dishwasher-safe beverage dispenser.

Planning notes

Door hinge not reversible.

Ideal installation height 95 cm to 145 cm (top edge of niche bottom).

Necessary lateral gap between appliance front and furniture panel of min. 5 mm.

The door panel surface of the appliance extends 21 mm from the furniture cavity.

When installing in a corner a side clearance is required.

Door opening angle appr. 110° (delivery status) - mounting distance to the wall has to be at least 350 mm.

Door opening angle appr. 155° - mounting distance to the wall has to be at least 650 mm.

Door opening angle appr. 92° - mounting distance to the wall has to be at least 100 mm (spare part No. 00636455).

Installation directly above 14 cm high warming drawer in 59 cm standardised niche.

The LAN port can be found at the back on the lower right side.

Special accessories (order as spare parts):

Part No. 17000706 Water filter Part No. region specific Descaling tablets Part No. region


specific Cleaning tablets Part No. 00636455

Door hinge restrictor (92° opening angle) Part No. 11015223 Bean container with lid

Connection

Total connected load 1.6 KW.
Connection cable 1.7 m with plug.
Plan a LAN cable.

Left corner installation



If using the 92° door hinge restrictor (spare part no. 00636455), the minimum distance from the wall is only 100 mm.

