



Fantini Cafe Kitchen Mixer &  
Pullout Spray

3629007901 — Chrome

#### Please note

- Connect hot and cold flexible hoses to isolation taps.
- Do not twist, kink or stretch flexible hoses (minimum bend radius 45mm).
- Hand tighten flexible hose connecting nuts, then apply quarter turn with a spanner.
- Supply pipe work must be flushed clean before installation.
- This is only an installation guide. Rogerseller recommends having the product on-site before commencing rough in.

## Specifications

It is a requirement of State Plumbing Codes that licensed plumbers carry out all tapware installations. All installations should comply with the relevant requirements of AS/NZS 3500 and local plumbing codes.

### Pressure:

[1] Maximum Hydrostatic Pressure: 1000kpa. This pressure may be exceeded only under test conditions as per AS/NZS 3500. Where hydrostatic pressure exceeds the maximum stated above, pressure-limiting valves should be installed. [2] Recommended Maximum Hydrostatic Pressure: 500kpa (AS/NZS 3500)

[3] Recommended Minimum Hydrostatic Pressure: 150kpa

### Temperature:

Maximum Water Temperature: 80° C. For optimum performance, hot and cold inlet water pressure should be equal.

## Care and Maintenance

[1] Product should be inspected for surface damage prior to installation. [2] Cleaning and handling of all finishes must be performed carefully. [3] Clean products using a soft cloth with warm soapy water only. [4] Never use harsh detergents or abrasive cleaners as these will damage the product. [5] Water marks can be removed from Matt Finishes with an application of a carnauba wax based non-abrasive polish on a microfibre cloth. [6] Do not use undue pressure when cleaning and wipe in one direction only. [7] Contact with harsh chemicals such as hair dye, hair bleach etc will result in damage to the finish. [8] Tapware should never be installed using acetone silicones. [9] Avoid the use of wax based furniture creams as this can result in a build up of deposits which will detract from the appearance. [10] Damage to finishes arising from improper installation or post installation use or failure to observe the above care and cleaning instructions will void all warranty agreements.

## Warranty

Rogerseller tapware, bathroom fittings and sanitary ware are covered by a five (5) year warranty from date of purchase. For full terms and conditions please refer to [rogerseller.com.au](http://rogerseller.com.au)

### Rogerseller Showrooms —

**Melbourne**  
173-177 Barkly Avenue  
Burnley VIC 3121  
P 03 9429 8888

**Sydney**  
18 Danks Street  
Waterloo NSW 2017  
P 02 8396 8700

**Brisbane**  
74-76 McLachlan Street  
Fortitude Valley QLD 4006  
P 07 3251 4333

### Concept Stores —

**Southern Innovations**  
(Fishwick ACT)  
P 02 6143 2666

**Southern Innovations**  
(Mitchell ACT)  
P 02 6129 7666

**Southern Innovations**  
(Albury NSW)  
P 02 6022 2777

**Routleys Plumbing Innovations**  
(Malvern SA)  
P 08 8291 3000

