


# Hambleton with Rinse

AUSH.4756



MODEL	CODE
● Hambleton with Rinse - Chrome	AUSH.4756CPWPC-3
● Hambleton with Rinse - Nickel	AUSH.4756NIWPC-3
● Hambleton with Rinse - Pewter	AUSH.4756PFWPC-3
● Hambleton with Rinse - English Bronze	AUSH.4756EBWPC-3
● Hambleton with Rinse - Satin Brass	AUSH.4756SBWPC-3
● Hambleton with Rinse - Polished Brass	AUSH.4756BRWPC-3
● Hambleton with Rinse - Gold	AUSH.4756IGWPC-3

Also Available: Hambleton (AUSH.4751) non spray-rinse model.



#### Features include:

- Handcrafted in the United Kingdom using premium low-lead brass
- Separate bench-mounted insulated spray rinse tap with 1.2m flexible hose
- White porcelain handles with Shaws insignia indices
- 1/4 turn German ceramic disc flow control
- Vernier insert for accurate handle alignment
- Supplied with dual check valve - ConServ DC 057
- 15 Year warranty. Please visit our website for individual finish warranties

#### Spray Rinse Requirements :

The spray rinse requires a minimum inlet water pressure of 100kPa, and a maximum of 500kPa to completely divert the water flow from the tap to the spray rinse.

Temperature range: Min 1°C. Max 70°C

Working Pressure: Min 1 Bar/15psi. Max 5 Bar/75psi

Packed Weight: 5.88kg

Flow Rates: 1 Bar: 6.2L/min

2 Bar: 9.9L/min

3 Bar: 12.7L/min

