

G 4930 SC Front Jubilee

Freestanding dishwasher

with 3D cutlery tray for maximum convenience at an attractive entry level price



- Save up to 40 % more electricity – hot water connection
- Versatility for all loads – 3D cutlery tray
- Every piece of crockery has its place – Miele basket design
- Very easy door opening and closing – ComfortClose

| Construction type | |
|---|-----------------------------|
| Freestanding dishwasher | • |
| 60 cm dishwasher | • |
| Design | |
| Colour | Stainless steel/CleanSteel |
| Control panel version | Straight fascia |
| Control type | Programme selector button |
| Display | 3-digit 7-segment indicator |
| Display colour | Yellow |
| Convenience | |
| Door closing aid | ComfortClose |
| Time left display | • |
| Delay start up to 24 hours | • |
| In-operation indicator light | Control indicator |
| Efficiency and sustainability | |
| Water consumption in the ECO programme in l | 11.3 |
| Water consumption in the Automatic programme in l from | 6.5 |
| Consumption values with ThermoSave® in ECO programme in kWh | 0.40 |
| Energy consumption in stand-by mode in W | 0.2 |
| Hot water connection | • |
| Alternating spray arm technology | • |
| Half load | • |
| Gentle treatment of crockery and glassware | |
| Recirculation Turbothermic drying | • |
| DetergentAgent | • |
| Wash programmes | |
| ECO | • |
| Automatic | • |
| Intensive 75 °C | • |
| Normal 55 °C | • |
| Gentle | • |
| Dishwashing options | |
| Short | • |
| Basket design | |
| Cutlery loading | 3D cutlery tray |
| Basket design | Comfort |
| Technology and quality | |
| Sensors | AutoSensor |
| Electronic professional pump for variable spray pressure | • |
| Safety | |
| Waterproof system | • |
| Safety lock | • |

G 4930 SC Front Jubilee

Freestanding dishwasher

with 3D cutlery tray for maximum convenience at an attractive entry level price



| Technical data | |
|---------------------------------|-------|
| Niche width in mm | 600 |
| Niche height in mm | 845 |
| Niche depth in mm | 600 |
| Appliance width in mm | 598 |
| Appliance height in mm | 845 |
| Appliance depth in mm | 600 |
| Depth with door open in cm | 119.5 |
| Net weight in kg | 54.5 |
| Total rated load in kW | 2.1 |
| Voltage in V | 230 |
| Fuse rating in A | 10 |
| Number of phases | 1 |
| Length of water drain hose in m | 1.50 |
| Length of supply lead in m | 1.90 |
| Length of water inlet hose in m | 1.50 |