

G 4930 U Jubilee

Built-under dishwashers

Delay start and countdown indicator for great entry-level value.



- Save up to 40 % more electricity – hot water connection
- Every piece of crockery has its place – Miele basket design
- Maximum versatility – Height-adjustable upper basket
- Very easy door opening and closing – ComfortClose

Construction type	
Built-under dishwasher	•
60 cm dishwasher	•
Design	
Colour	Stainless steel/CleanSteel
Control panel version	Straight fascia
Control type	Programme selector button
Display	3-digit 7-segment indicator
Display colour	Yellow
Convenience	
Door closing aid	ComfortClose
Time left display	•
Delay start up to 24 hours	•
In-operation indicator light	Control indicator
Efficiency and sustainability	
Water consumption in the ECO programme in l	11.3
Water consumption in the Automatic programme in l from	6.5
Consumption values with ThermoSave® in ECO programme in kWh	0.41
Energy consumption in stand-by mode in W	0.2
Hot water connection	•
Alternating spray arm technology	•
Half load	•
Gentle treatment of crockery and glassware	
Recirculation Turbothermic drying	•
DetergentAgent	•
Wash programmes	
ECO	•
Automatic	•
Intensive 75 °C	•
Normal 55 °C	•
Gentle	•
Dishwashing options	
Short	•
Basket design	
Cutlery loading	Cutlery basket
Basket design	Comfort
Technology and quality	
Sensors	AutoSensor
Electronic professional pump for variable spray pressure	•
Safety	
Waterproof system	•
Safety lock	•

G 4930 U Jubilee

Built-under dishwashers

Delay start and countdown indicator for great entry-level value.



Technical data	
Niche width in mm	600
Niche height in mm	805
Niche depth in mm	570
Appliance width in mm	598
Appliance height in mm	805
Appliance depth in mm	570
Depth with door open in cm	116.5
Net weight in kg	44.0
Total rated load in kW	2.1
Voltage in V	230
Fuse rating in A	10
Number of phases	1
Length of water drain hose in m	1.50
Length of supply lead in m	1.90
Length of water inlet hose in m	1.50