## **Built-in Dishwashers**



## G 6827 SCi XXL

Integrated dishwasher XXL with 3D cutlery tray+ and in-door salt container for maximum convenience.



- Perfect results in less than one hour QuickPowerWash
- Easiest-ever communication with the appliance – WiFi Conn@ct
- Perfect illumination for easy loading BrilliantLight
- Convenient salt replenishment Indoor salt container
- All safely loaded where needed Maxi comfort basket design

Construction type	
Semi-integrated dishwasher	•
60 cm dishwasher	•
XXL dishwasher	•
Design	
Colour	Stainless steel/CleanSteel
Control panel version	Slanted fascia
Control type	Programme selector buttor
Display	1-line text display
Display colour	White
MultiLingua	•
Convenience	
Door closing aid	ComfortClose
Time left display	•
BrilliantLight	•
In-door salt container	•
Delay start up to 24 hours	•
In-operation indicator light	Display
Display language selection	• Biopidy
Efficiency and sustainability	
Water consumption in the ECO programme in I	11.1
Water consumption in the Automatic programme in I from	6.5
Consumption values with ThermoSave® in ECO	
programme in kWh	0.34
Energy consumption in stand-by mode in W	0.2
FlexiTimer with EcoStart	•
Hot water connection	•
EcoFeedback	•
Alternating spray arm technology	•
Half load	•
Gentle treatment of crockery and glassware	
AutoOpen drying	•
SensorDry	•
Recirculation Turbothermic drying	•
Perfect GlassCare	•
DetergentAgent	•
Wash programmes	
ECO	•
Automatic	•
Intensive 75 °C	•
Normal 55 °C	•
Gentle	•
QuickPowerWash	•
Hygiene	•
SolarSave	•
ExtraQuiet 38 dB(A)	•
Tall items 65°C	<u>•</u>
Maintenance wash	-

## **Built-in Dishwashers**



## G 6827 SCi XXL

Integrated dishwasher XXL with 3D cutlery tray+ and in-door salt container for maximum convenience.



Dishwashing options	
Short	•
Intensive lower basket	- <del>-</del>
Extra economical	_
Extra dry	_
Basket design	
Cutlery loading	3D cutlery tray+
FlexCare glass holder	4
Basket design	- MaxiComfort
Appliance networking	Mark Samuel
Miele@home	•
WiFiConn@ct	•
SmartStart	•
MobileControl	•
ShopConn@ct	•
Technology and quality	
Sensors	AutoSensor
EcoTech heat exchanger	•
Electronic professional pump for variable spray pressure	•
Safety	
Waterproof system	•
Filter indicator light	•
Safety lock	•
Technical data	
Niche width in mm	600
Niche width in mm Niche height in mm	845
Niche height in mm	845
Niche height in mm Niche depth in mm	845 570
Niche height in mm Niche depth in mm Appliance width in mm	845 570 598
Niche height in mm Niche depth in mm Appliance width in mm Appliance height in mm	845 570 598 845
Niche height in mm Niche depth in mm Appliance width in mm Appliance height in mm Appliance depth in mm	845 570 598 845 570
Niche height in mm Niche depth in mm Appliance width in mm Appliance height in mm Appliance depth in mm Depth with door open in cm	845 570 598 845 570 120.5
Niche height in mm Niche depth in mm Appliance width in mm Appliance height in mm Appliance depth in mm Depth with door open in cm Net weight in kg	845 570 598 845 570 120.5 48.7
Niche height in mm Niche depth in mm Appliance width in mm Appliance height in mm Appliance depth in mm Depth with door open in cm Net weight in kg Total rated load in kW	845 570 598 845 570 120.5 48.7 2.1 230 10
Niche height in mm Niche depth in mm Appliance width in mm Appliance height in mm Appliance depth in mm Depth with door open in cm Net weight in kg Total rated load in kW Voltage in V	845 570 598 845 570 120.5 48.7 2.1 230
Niche height in mm Niche depth in mm Appliance width in mm Appliance height in mm Appliance depth in mm Depth with door open in cm Net weight in kg Total rated load in kW Voltage in V Fuse rating in A	845 570 598 845 570 120.5 48.7 2.1 230 10
Niche height in mm Niche depth in mm Appliance width in mm Appliance height in mm Appliance depth in mm Depth with door open in cm Net weight in kg Total rated load in kW Voltage in V Fuse rating in A Number of phases	845 570 598 845 570 120.5 48.7 2.1 230 10
Niche height in mm Niche depth in mm Appliance width in mm Appliance height in mm Appliance depth in mm Depth with door open in cm Net weight in kg Total rated load in kW Voltage in V Fuse rating in A Number of phases Energy stars	845 570 598 845 570 120.5 48.7 2.1 230 10 1 4.5
Niche height in mm Niche depth in mm Appliance width in mm Appliance height in mm Appliance depth in mm Depth with door open in cm Net weight in kg Total rated load in kW Voltage in V Fuse rating in A Number of phases Energy stars Water stars	845 570 598 845 570 120.5 48.7 2.1 230 10 1 4.5 5.5