

H 6461 BP

Ovens

with intuitive touch operation and Moisture Plus for perfect results.



- TFT text display with touch operation

 DirectSensor
- Perfect baking and roasting results Moisture Plus
- The simple way to perfect results Automatic programmes
- Minimal cleaning effort Pyrolytic cleaning

Construction type	
Built-in oven	•
Design	
PureLine	•
Colour	Stainless steel/Clean Steel
Display	DirectSensor
Convenience features	
Precise temperature regulation	30 - 300°C
Operating modes	
Defrosting	<u>•</u>
Automatic programmes	More than 60
Auto roast	•
Gentle bake	•
Grill	•
Fan plus	•
Intensive bake	•
Moisture plus	•
Conventional heat	•
Bottom heat	•
Fan grill	•
Special applications	•
User convenience	
MultiLingua	•
DirectSelection of operating modes	•
Timed steam bursts programmable	•
Time of day display	
Date display	
Minute minder	
Clock buffer in h	300
	200
Start-stop programming	<u>•</u>
Safety switch-off	<u>•</u>
Programmable cooking duration	<u>•</u>
Actual temperature display	<u>•</u>
Recommended temperature	<u>•</u>
Buzzer when desired temperature is reached	<u>•</u>
User programmes	20
Individual settings	•
Door	
CleanGlass door	<u> </u>
Door contact switch	•
Door hinge	Bottom
Oven compartment	
Oven compartment volume in I	76
No. of shelf levels	5
Numbered shelf levels	•
No. of halogen lamps	1
Cleaning convenience	
Stainless steel front with CleanSteel finish	•
Pyrolytic self-cleaning	•
Unheated catalyser	•
Hinged grill heater element	•



H 6461 BP

Ovens

with intuitive touch operation and Moisture Plus for perfect results.



Efficiency and sustainability	
Energy-saving lighting	<u> </u>
Residual heat utilisation	•
Rapid heat-up	•
Safety	
Appliance cooling system and touch-cool fronts	•
Safety switch-off	
System lock	•
Door lock during pyrolytic cleaning	•
Technical data	
Niche width in mm	560
Niche height in mm	593
Niche depth in mm	550
Appliance width in mm	554
Appliance height in mm	579
Appliance depth in mm	547
Weight in kg	47.0
Total rated load in kW	3.5
Voltage in V	230
Fuse rating in A	16
Number of phases	1
Standard accessories	
Universal tray with PerfectClean	1
Baking tray with PerfectClean	1
Baking and roasting rack PyroFit	2
Recipe booklet	•
Mains cable	•
Descaling tablets	•





H 6461 BP

Ovens

with intuitive touch operation and Moisture Plus for perfect results.








H 5000 EP/BP - 60 cm (Installation drawing)

- * Appliances with glass front ** Appliances with metal front

Detailed installation drawing H 6000,H 5000, H 4000, E/B, EP/BP, 76 litres, (Installation drawing)

A = Design "ContourLine": 45 mm Design "PureLine": 42 mm B = Appliances with glass front: 2,2 Appliances with metal front: 1,2



 $\rm H\,5000\;BP;\,H\,6000\;BP;\,H\,2000\;BP;\,60\;cm$ (Installation drawing)

- * Appliances with glass front ** Appliances with metal front