

H 6461 BP

Ovens

with intuitive touch operation and Moisture Plus for perfect results.



- TFT text display with touch operation

 DirectSensor
- Perfect baking and roasting results Moisture Plus
- The simple way to perfect results Automatic programmes
- Minimal cleaning effort Pyrolytic cleaning

Brilliant white DirectSensor 30 - 300°C More than 60
DirectSensor 30 - 300°C More than 60
DirectSensor 30 - 300°C More than 60
DirectSensor 30 - 300°C More than 60
30 - 300°C More than 60 •
More than 60
More than 60
•
•
•
•
•
•
•
•
•
•
•
`
`
•
200
<u> </u>
20
•
<u> </u>
<u>•</u>
Bottom
76
5
<u> </u>
1
<u> </u>
•



H 6461 BP

Ovens

with intuitive touch operation and Moisture Plus for perfect results.



Efficiency and sustainability	
Energy-saving lighting	•
Residual heat utilisation	•
Rapid heat-up	•
Safety	
Appliance cooling system and touch-cool fronts	•
Safety switch-off	•
System lock	•
Door lock during pyrolytic cleaning	•
Technical data	
Niche width in mm	560
Niche height in mm	593
Niche depth in mm	550
Appliance width in mm	554
Appliance height in mm	579
Appliance depth in mm	547
Weight in kg	47.0
Total rated load in kW	3.5
Voltage in V	230
Fuse rating in A	16
Number of phases	1
Standard accessories	
Universal tray with PerfectClean	1
Baking tray with PerfectClean	1
Baking and roasting rack PyroFit	1
Recipe booklet	•
Mains cable	•
Descaling tablets	•





H 6461 BP

Ovens

with intuitive touch operation and Moisture Plus for perfect results.








H 5000 EP/BP - 60 cm (Installation drawing)

- * Appliances with glass front ** Appliances with metal front

Detailed installation drawing H 6000,H 5000, H 4000, E/B, EP/BP, 76 litres, (Installation drawing)

A = Design "ContourLine": 45 mm Design "PureLine": 42 mm B = Appliances with glass front: 2,2 Appliances with metal front: 1,2



 $\rm H\,5000\;BP;\,H\,6000\;BP;\,H\,2000\;BP;\,60\;cm$ (Installation drawing)

- * Appliances with glass front ** Appliances with metal front