

H 6660 BP

Ovens

with AirClean catalyser and food probe for precise cooking.



- TFT clear text display with touch operation SensorTronic
- Perfect baking and roasting results Moisture Plus
- Precise temperature-controlled roasting Food probe
- The simple way to perfect results Automatic programmes
- Minimal cleaning effort Pyrolytic cleaning

Construction type	
Built-in oven	•
Design	
PureLine	•
Colour	Stainless steel/Clean Stee
Display	SensorTronic
Convenience features	
Precise temperature regulation	30 - 300°C
Food probe	•
Crisp function	•
Operating modes	
Defrosting	•
Automatic programmes	More than 100
Auto roast	•
Gentle bake	•
Grill	•
Economy grill	•
Fan plus	•
Intensive bake	•
Moisture plus	
Low temperature cooking	
Conventional heat	-
Top heat	-
Bottom heat	`
	`
Fan grill	
Special applications	
User convenience	•
MultiLingua	`
Timed steam bursts programmable	`
Time of day display	<u>•</u>
Date display	
Minute minder	•
Clock buffer in h	200
Start-stop programming	<u>•</u>
Safety switch-off	
Programmable cooking duration	<u> </u>
Value entry via number pad	<u> </u>
Actual temperature display	<u> </u>
Recommended temperature	<u> </u>
Buzzer when desired temperature is reached	<u> </u>
User programmes	20
Sabbath programme	•
Individual settings	•
Door	
CleanGlass door	•
Door contact switch	•
Door hinge	Bottom



H 6660 BP

Ovens

with AirClean catalyser and food probe for precise cooking.



Oven compartment	
Oven compartment volume in I	76
No. of shelf levels	5
Numbered shelf levels	•
No. of halogen lamps	double
Cleaning convenience	
Stainless steel front with CleanSteel finish	<u> </u>
Pyrolytic self-cleaning	
Heated catalyser	•
Hinged grill heater element	•
Efficiency and sustainability	
Energy-saving lighting	<u> </u>
Residual heat utilisation	
Rapid heat-up	•
Safety	
Appliance cooling system and touch-cool fronts	<u> </u>
Safety switch-off	<u> </u>
System lock	•
Door lock during pyrolytic cleaning	<u>•</u>
Technical data	
Niche width in mm	560
Niche height in mm	593
Niche depth in mm	550
Appliance width in mm	554
Appliance height in mm	579
Appliance depth in mm	547
Weight in kg	47.0
Total rated load in kW	3.7
Voltage in V	230
Fuse rating in A	16
Number of phases	1
Standard accessories	
Universal tray with PerfectClean	1
Baking tray with PerfectClean	1
Baking and roasting rack PyroFit	2
Recipe booklet	<u> </u>
Mains cable	<u>•</u>
Descaling tablets	•





H 6660 BP

Ovens

with AirClean catalyser and food probe for precise cooking.








H 5000 EP/BP - 60 cm (Installation drawing)

- * Appliances with glass front ** Appliances with metal front

Detailed installation drawing H 6000,H 5000, H 4000, E/B, EP/BP, 76 litres, (Installation drawing)

A = Design "ContourLine": 45 mm Design "PureLine": 42 mm B = Appliances with glass front: 2,2 Appliances with metal front: 1,2



 $\rm H\,5000\;BP;\,H\,6000\;BP;\,H\,2000\;BP;\,60\;cm$ (Installation drawing)

- * Appliances with glass front ** Appliances with metal front