Induction Cooktops



KM 6381

Induction cooktop with onset controls with panorama cooking zone arrangement for the maximum cooking convenience.

Easy to clean ceramic glass



- Fast selection w. numerical linear keybanks – Direct control plus
- Premium design 916mm wide with bevelled edges all round
- Versatile and fast 4 cooking zones incl. 2 PowerFlex zones
- Communication with rangehood automatic function Con@ctivity 2.0
- Broad performance spectrum keeping warm function & TwinBooster

| 0 | |
|---|--------------------------|
| Heating type | |
| Heating type | Induction |
| Construction type | |
| Independent of cooker | • |
| Design | |
| Elegant glass ceramic surface | <u> </u> |
| Ceramic surface colour | Black |
| Print design | LightPrint |
| Bevelled edges | Bevel-edges on all sides |
| Cooking zone details | |
| Number of cooking zones | 4 |
| PowerFlex cooking zones | |
| No. | 4 |
| Diameter in mm | 150x230 |
| Rating in W | 2.100 |
| Booster in W | 3.000 |
| TwinBooster in W | 3650 |
| Cooking zone | |
| Position | left centre |
| Type | PowerFlex bridge |
| Diameter in mm | 230x390 |
| Rating in W | 3400 |
| Booster in W | 4800 |
| TwinBooster in W | 7300 |
| Position | right |
| Type | PowerFlex bridge |
| Diameter in mm | 230x390 |
| Rating in W | 3400 |
| Booster in W | 4800 |
| TwinBooster in W | 7300 |
| User convenience | |
| Operation via sensor controls | Direct selection |
| Pan and pan size recognition | • |
| Stop & Go function | • |
| Minute minder | • |
| Safety switch-off | • |
| Auto heat-up | • |
| Keeping warm | • |
| Individual setting options (e.g. buzzers) | • |
| Displays | |
| Digital power level display | • |
| Appliance networking | |
| Automatic function Con@ctivity 2.0 | • |
| Cleaning convenience | |
| | |

Induction Cooktops



KM 6381

Induction cooktop with onset controls with panorama cooking zone arrangement for the maximum cooking convenience.



| Safety | |
|---|-----|
| Safety switch-off | • |
| Lock function | • |
| System lock | • |
| Fault monitoring | • |
| Integrated cooling fan | • |
| Overheating protection | • |
| Residual heat indicator | • |
| Technical data | |
| Dimensions in mm (width) | 916 |
| Dimensions in mm (depth) | 416 |
| Casing height incl. connection box in mm | 47 |
| Cutout dimensions in mm (width) with surface-mounted installation | 886 |
| Cutout dimensions in mm (depth) with surface-mounted installation | 386 |
| Voltage in V | 230 |
| Total rated load in kW | 7.3 |
| Weight in kg | 12 |
| Length of supply lead in m | 1.4 |
| Standard accessories | |
| Mains cable | • |


Induction Cooktops



KM 6381

Induction cooktop with onset controls with panorama cooking zone arrangement for the maximum cooking convenience.





KM6381 (installation drawing)

- Front
 Casing depth
 Minisconnection oint
 Mains connection box. Mains connection cable, L = 1440 mm supplied loose