Professional Washing Machines, Tumble Miele Dryers



PT 7188 Vario EL

Vented dryer, electric With the shortest cycle of 37 minutes for a high throughput of laundry.



- Drum volume 180 I, load capacity 10.0 kg
- Large programme variety application-specific drying programmes
- Precision drying of all fabrics - PerfectDry
- Unique, gentle fabric care patented honeycomb drum
- Easy operation viewing window and large-surface filter

os for a riight throughput of launary.	
Construction type and version	
Construction type	Front loader
Front	Stainless steel
Load in kg	10.0
Load ratio	1:22,5
Drum volume in I	180
Drying system	Vented
Door opening angle in degrees	180
Door hinge	left
Patented honeycomb drum	•
Application	
Suitable for domestic use	•
Performance data	
Maximum evaporation capacity in I/hour	8.1
Programme duration in min.	37
Tested operating hours	20,000
Controls	
Control system	Profitronic L Vario
Programmability	programmable
Lleavintoviace	Residual moisture
User interface	controlled
Max. delay start in h	24
Time left display	•
Programme sequence indicator	•
Fascia panel with plain text	•
Selectable display languages	•
Standard electrical connection	
Heating type	Electrical
Electric heater rating in kW	5,22-5,68
Total connected load in kW	5,78-6,24
Fuse rating in A	25
Dimensions and weight	
External dimensions, height in mm	1,020
External dimensions, width in mm	700
External dimensions, depth in mm	763
Net weight in kg	77
Maximum floor loading in N	1000
Emissions data	
Emissions – sound pressure at workplace	<70 dB(A) re 20 μPa
Features	
Intelligent drum reversal	•
Axial airflow	<u> </u>
Large-surface filter	<u> </u>
PerfectDry	•
SoftLift drum ribs	•
Low temperature function	•
Communication slot	•
Tumble dryer basket	•
Drum lighting	•
Machine-independent accessories	•

Professional Washing Machines, Tumble Miele Dryers



PT 7188 Vario EL

Vented dryer, electric With the shortest cycle of 37 minutes for a high throughput of laundry.



Connection options	
Payment system	<u> </u>
Serial interface RS 232 (optional)	•
Optical interface for service access	•
Peak load cut-out/energy management (optional)	•
Capacities	
Respirator masks [number]	4
Overalls [number]	1
Over jackets [number]	1-2
Synthetic duvets [number]	1
Synthetic pillows [number]	1-2
Down duvets [number]	1
Down pillows [number]	_1-2
Cloths, 22 g [number]	182
Cotton mops, 40 cm [number]	42
Cotton mops, 50 cm [number]	36
Microfibre mops, 40 cm [number]	66
Microfibre mops, 50 cm [number]	47
Summer horse blankets [number]	1-2
Test certificate	
CE	•
VDE	•
Splash-proof safety rating IPX4	•
WEEE	•
Energysafe	•
Energy star rating	<u> </u>
RCM	•
Complies with Machinery Directive 2006/42/EC	•