

## TMR840 WP SFinish&Eco XL

T1 Heat-pump tumble dryer

up to 9 kg load capacity - perfect drying results even for large laundry loads.



- Fragrant laundry just the way you like it – FragranceDos
- The quick alternative to ironing w. steam smoothing – SteamFinish
- Precision drying of all textiles – PerfectDry
- Cost-efficient, powerful, and no wear and tear – ProfiEco Motor

<b>Construction type</b>	
Suitable for stacking	•
Side-by-side	•
Slot-in	•
Door hinge	left
<b>Model</b>	
Heat pump dryer	•
<b>Design</b>	
Appliance colour	Lotus white
Control panel colour	Lotus white
Parameter buttons	Chrome
Extra option buttons	Chrome
Rotary selector colour	Lotus white cap/chrome ring
Control panel version	5° incline
Control type	Rotary selector
Display	4 line TFT
<b>Drying results</b>	
FragranceDos	•
Perfect Dry	•
SteamFinish	•
Intelligent drum reversal	•
<b>Gentle laundry care</b>	
Patented honeycomb drum	•
<b>User convenience</b>	
Delay start up to 24 hours	•
Time left display	•
Time of day display	•
Programme sequence indicator	•
Favourite programmes	•
Drum lighting	LED
Choice of language	•
Condensate container	•
Integrated condensed water drainage	•
<b>Efficiency and sustainability</b>	
Maintenance-free heat exchanger	•
EcoFeedback function	•
EcoDry technology	•
ProfiEco motor	•

## TMR840 WP SFinish&Eco XL

T1 Heat-pump tumble dryer

up to 9 kg load capacity - perfect drying results even for large laundry loads.



<b>Drying programmes</b>	
Automatic plus	•
Cottons (coloureds)	•
Minimum iron	•
Delicates	•
Shirts	•
Silks handcare	•
Woolens handcare	•
Steam smoothing	•
Mixed items	•
Favourites	•
Express	•
Denim	•
Outerwear	•
Proofing	•
Sportswear	•
Standard pillows	•
Cool air	•
Warm air	•
Basket programme	•
Gentle smoothing	•
<b>Drying options</b>	
Anti-crease	•
Gentle tumble	•
Freshen up	•
Buzzer	•
Automatic load control	•
<b>Quality</b>	
Enamelled front	•
Soft ribs	•
<b>Safety</b>	
PIN code lock	•
"Empty out container" indicator	•
"Clean filter" indication	•
Optical interface	•
<b>Technical data</b>	
Dimensions in mm (width)	596
Dimensions in mm (height)	850
Dimensions in mm (depth)	643
Appliance depth in mm with opened door	1,077
Weight in kg	62
Total rated load in kW	1.1
Voltage in V	230
Fuse rating in A	10
Length of supply lead in m	2
Contains fluorinated greenhouse gases	•
Hermetically sealed	•
Type of coolant	R134a