## **Tumble Dryers**



## TMV 840 WP SFinish&Eco XL Tronic AU

T1 Heat-pump tumble dryer with 8 star energy rating & 9kg load - best energy effiency even for large items



- Intuitive operation thanks to convenient touch displays
- Fragrant laundry just the way you like it – FragranceDos
- The quick alternative to ironing w. steam smoothing SteamFinish
- Precision drying of all textiles PerfectDry

Construction type	
Suitable for stacking	•
Side-by-side	•
Slot-in	•
Door hinge	left
Model	
Heat pump dryer	•
Design	
Appliance colour	Lotus white
Control panel colour	Lotus white
Colours of controls	Chrome
Control panel version	5° incline
Control type	Touch controls
Display	Touchtronic
Drying results	
FragranceDos	<u> </u>
Perfect Dry	•
SteamFinish	•
Intelligent drum reversal	•
Gentle laundry care	
Patented honeycomb drum	•
User convenience	
Delay start up to 24 hours	<u>•</u>
Time left display	<u>•</u>
Programme sequence indicator	•
Drying assistant	•
Information text	•
Favourite programmes	•
Drum lighting	LED
Choice of language	•
Condensate container	•
Integrated condensed water drainage	•
Efficiency and sustainability	
Maintenance-free heat exchanger	•
EcoFeedback function	•
EcoDry technology	•
ProfiEco motor	•

## **Tumble Dryers**



## TMV 840 WP SFinish&Eco XL Tronic AU

T1 Heat-pump tumble dryer with 8 star energy rating & 9kg load - best energy effiency even for large items



Drying programmes	
Automatic plus	•
Cottons (coloureds)	<u> </u>
Minimum iron	
Delicates	<del>-</del>
Shirts	<del>-</del>
Silks handcare	<del>-</del>
Woollens handcare	•
Steam smoothing	•
Mixed items	•
	<del>`</del>
Express  Denim	
	•
Outerwear	
Proofing	<u>•</u>
Sportswear	<u>•</u>
Standard pillows	<u> </u>
Cottons hygiene	<u> </u>
Cool air	<u>•</u>
Warm air	<u> </u>
Basket programme	<u>•</u>
Gentle smoothing	•
Drying options	
Anti-crease	<u>•</u>
Gentle tumble	<u>•</u>
Freshen up	<u>•</u>
Buzzer	•
Automatic load control	•
Quality	
Enamelled front	•
Soft ribs	•
Safety	
PIN code lock	<u>•</u>
"Empty out container" indicator	<u>•</u>
"Clean filter" indication	<u>•</u>
Optical interface	•
Technical data	
Dimensions in mm (width)	596
Dimensions in mm (height)	850
Dimensions in mm (depth)	643
Appliance depth in mm with opened door	1,077
Weight in kg	61
Total rated load in kW	1.1
Voltage in V	230
Fuse rating in A	10
Length of supply lead in m	2
Contains fluorinated greenhouse gases	•
Hermetically sealed	•
Type of coolant	R134a
Standard accessories	
Fragrance flacon	•