Washing Machines



WDD030 EcoPlus&Comfort

W1 Classic front-loading washing machine

for 1-8 kg of laundry - Miele quality and efficiency at an attractive price.



- Miele quality tested for the equivalent of 20 years' use*
- Easy fingertip operation DirectSensor
- Perfect supplement for specific applications CapDosing
- Gentle laundry care thanks to the Miele honeycomb drum
- Cost-efficient, powerful & no wear and tear – the ProfiEco Motor

Construction type	
Suitable for stacking	•
Side-by-side	•
Slot-in	•
Door hinge	right
Model	
Front-loader	•
Spinning	
Rinse hold	•
"Without spin" function	•
Design	
Appliance colour	Lotus white
Control panel colour	Lotus white
Rotary selector colour	Lotus white
Control panel version	Slanted
Control type	Rotary selector
Display	DirectSensor yellow, 7 segment
Cleaning performance	
CapDosing	•
Gentle laundry care	
Patented honeycomb drum	•
User convenience	
Delay start up to 24 hours	<u> </u>
Time left display	•
AutoClean detergent drawer	•
Efficiency and sustainability	
More economical than the threshold value for energy efficiency rating A+++	10%
Automatic load control	•
Low temperature wash "Cold" and "20 °C"	•
Flow meter	`
Foam sensing	·
ProfiEco motor	
Wash programmes	-
Cottons (coloureds)	•
Minimum iron	<u> </u>
Delicates	•
Shirts	•
Woollens (hand-washable)	
Express 20	-
Dark garments / Denim	`
Outerwear	
Proofing	_ `
Cottons Eco	_ `
Separate rinse/Starch	_ `
•	
Drain / Spin	•

Washing Machines



WDD030 EcoPlus&Comfort

W1 Classic front-loading washing machine

for 1-8 kg of laundry - Miele quality and efficiency at an attractive price.



W 1	
Wash options	
Short	
Soak	<u>•</u>
Pre-wash	<u>•</u>
Water plus	<u> </u>
Additional rinse cycle	<u> </u>
Quality	
Suds container	Stainless Steel
Enamelled front	•
Counterweights made of cast iron	•
Safety	
Water control system	<u> </u>
PIN code lock	
Optical interface	•
Technical data	
Dimensions in mm (width)	596
Dimensions in mm (height)	850
Dimensions in mm (depth)	636
Appliance depth in mm with opened door	1,054.0
Weight in kg	90.00
Total rated load in kW	2.300
Voltage in V	230
Fuse rating in A	10
Length of supply lead in m	2