Washing Machines



WKB 130

W1 Front-loading washing machine With Softsteam honeycomb drum and CapDosing for perfect laundry care

Buzzer



- Ironing made easy SoftSteam honeycomb drum with pre-ironing
- Perfect supplement for specific applications – CapDosing
- Cost-efficient, powerful & no wear and tear the ProfiEco Motor
- Wash any load w. energy efficiency Automatic load recognition
- Laundry care on schedule Delay start and countdown indicator

and CapDosing for perfect laundry care	
Construction type	
Suitable for stacking	•
Side-by-side	•
Slot-in	•
Door hinge	right
Model	
Product brand	W1 Chrome Edition
Front-loader	•
Spinning	
Rinse hold	•
"Without spin" function	•
Design	
Appliance colour	Lotus white
Control panel colour	Lotus white
Parameter buttons	Lotus white
Extra option buttons	Lotus white
Rotary selector colour	Lotus white
Control panel version	Slanted
Control type	Rotary selector
Display	1 line
Cleaning performance	
CapDosing	•
Gentle laundry care	
SoftSteam drum	•
User convenience	
Delay start up to 24 hours	<u> </u>
Time left display	<u> </u>
Programme sequence indicator	•
Choice of language	•
AutoClean detergent drawer	•
Efficiency and sustainability	
Automatic load control	<u>•</u>
Low temperature wash "Cold" and "20 °C"	<u> </u>
Flow meter	<u> </u>
Foam sensing	<u>•</u>
ProfiEco motor	<u>•</u>
Wash programmes	
Cottons (coloureds)	
Minimum iron	<u>•</u>
Delicates	<u>•</u>
Cottons with pre-wash	<u> </u>
Shirts	<u>•</u>
Woollens (hand-washable)	<u>•</u>
Express 20	<u>•</u>
Dark garments / Denim	<u>•</u>
Separate rinse/Starch	<u>•</u>
Wash options	
Short	
Water plus	<u>•</u>
Additional rinse cycle	<u> </u>
Pre-ironing	<u> </u>

Washing Machines



WKB 130

W1 Front-loading washing machine With Softsteam honeycomb drum and CapDosing for perfect laundry care



Quality	
Suds container	Stainless Steel
Enamelled front	•
Counterweights made of cast iron	•
Safety	
Water control system	•
Safety lock	•
PIN code lock	•
Optical interface	•
Technical data	
Dimensions in mm (width)	596
Dimensions in mm (height)	850
Dimensions in mm (depth)	636
Appliance depth in mm with opened door	1,054.0
Weight in kg	94.00
Total rated load in kW	2.300
Voltage in V	230
Fuse rating in A	10
Length of supply lead in m	2